MANEUVERING CONTROL OF REPLENISHMENT AT SEA

Theodoros Sarzetakis

LIBRARY
NAVAL POSTGRADUATE SCHOOL
MONTEREY, CALIF. 93940

NAVAL POSTGRADUATE SCHOOL
Monterey, California

THESIS

MANEUVERING CONTROL OF REPLENISHMENT AT SEA

by

Theodoros Sarzetakis

Thesis Advisor: G. J. Thaler

September 1972

Approved for public release; distribution unlimited.

T149351

Maneuvering Control of Replenishment at Sea

by

Theodoros Sarzetakis
Lieutenant, Hellenic Navy
B.S., Naval Postgraduate School, 1972

Submitted in partial fulfillment of the
requirements for the degree of

MASTER OF SCIENCE IN ELECTRICAL ENGINEERING

from the

NAVAL POSTGRADUATE SCHOOL
September 1972

Thesis
S 68
c.2

LIBRARY
NAVAL POSTGRADUATE SCHOOL
MONTEREY, CALIF. 93940

ABSTRACT

An investigation of the maneuvering control of ships involved in the replenishment at sea operation under calm water conditions is carried out.

The linearized differential equations of motion of a vessel in the horizontal plane are established and implemented for the formation of computer programs, useful for the study of the behavior and stability of the ship with and without the influence of control surfaces (rudders).

Three methods of controlling automatically the maneuvering of two ships, in replenishment at sea, under the influence of interactive forces and moments, based on the classical feedback control theory are presented, compared and conclusions are finally drawn about the efficiency of these methods.

TABLE OF CONTENTS

I. INTRODUCTION ---------- 6

II. THE INTERACTION EFFECTS ---------- 8

A. NEWTON'S EXPERIMENT ---------- 8

III. EQUATIONS OF MOTION ---------- 14

A. THE GENERAL CASE ---------- 14

B. THE HORIZONTAL PLANE MOTION ---------- 16

1. Linearization of the Horizontal Plane Equations ---------- 17

2. Nondimensionalization of the Horizontal Plane Equations ---------- 19

3. Manipulation of the Equations for Computer Simulation ---------- 21

4. Stability Investigation ---------- 25

5. The Transfer Functions ---------- 31

IV. THE CONTROL LOOPS ---------- 35

A. PATHKEEPING LOOP ---------- 35

1. The Block Diagram ---------- 35

2. Determination of K and K_t for a Desired Performance ---------- 35

3. Computer Simulation of the Controlled Plant ---------- 38

B. THE DISTANCE KEEPING LOOP ---------- 43

1. A Special Case ---------- 43

2. Computer Program for the Controlled Plant ---------- 46

3. Determination of K and K_t for a Desired Performance ---------- 48

4. Computer Simulation ---------- 50

V. ACTUAL REPLENISHMENT AT SEA PROBLEM ---------- 57

A. INCLUSION OF INTERACTION FORCES AND MOMENTS -- 57

1. Characteristic Values ---------- 57

2. Modification of the Equations of Motion -- 59

3. The Behavior of the Ships Under the Influence of Interacting Forces and Moments Without Controls ---------- 63

B. THE PROPOSED METHODS OF CONTROL ---------- 63

1. Method I ---------- 63

2. Method II ---------- 66

3. Method III ---------- 69

VI. CONCLUSIONS ---------- 87

LIST OF REFERENCES ----------108

INITIAL DISTRIBUTION LIST ----------109

FORM DD 1473 ----------110

ACKNOWLEDGEMENT

The author wishes to express his deep respect and appreciation to Dr. George Thaler, under whose warm and wise guidance this thesis was completed. He is also deeply indebted to A. T., the great man and real friend, who made it all possible.

I. INTRODUCTION

Replenishment-at-sea operations are conducted for the purpose of safe transferring of the maximum amount of cargo in a minimum of time between ships of the fleet, in order to enable them to operate at sea for prolonged periods. As the cargo must be guided and controlled during the transfer operation, a suitable physical connection (rigs) must be established and maintained between the two ships as they travel along with identical speeds. This connection requires that the ships operate at close quarters, a fact that makes maneuvering during replenishment a critical and dangerous operation.

The maneuver involves six factors: course, speed, distance between ships, the approach, station keeping and departure.

In this thesis the very important phase of maintaining station will mainly be considered. Maintaining station alongside the delivery ship requires precise maneuvering on the part of the receiving ship. Steaming too close restricts maneuverability and steaming too far apart puts an undue strain on the rigs. Steaming too close increases also the turbulence between the ships.

Maneuvering at close proximity does not really by itself present such a great navigational problem, but steaming alongside results in certain hydrodynamic phenomena that create unpredicted interactive forces and moments between the ships that generate the ever existing danger of collision.

Replenishment of warships (mainly with fuel from tankers), is a procedure which is nowadays regarded as commonplace and accompanied by little, risk once the vessels have taken up station close aboard. Yet the fact that collisions in open deep water occurred and they still unfortunately do, in spite of modern navigational aids, gives rise to the question as to what part interaction affects may have played in the accidents.

It has been already stated that maintaining station alongside requires precise maneuvering on the part of the receiving ship. This, according to the tactical requirements of the operation is interpreted as follows:

The replenishing ship is responsible for course keeping only.

The receiving ship is responsible for both course and station (distance between ships) keeping.

On this very basis, this thesis attempts the investigation of the automatic maneuvering control of two individual ships in a replenishment at sea operation, under calm water conditions. It first presents the interaction affects problem, and then it establishes the equation of motion for one ship and the development of its mathematical model. Next, it investigates the stability and behavior of the individual ship in motion without controls and proceeds with the presentation and investigation of two major control loops – the course keeping loop and the distance keeping one. Finally, those loops are implemented in certain ways in a somewhat realistic replenishment at sea problem for three different proposed techniques of the operation for which computer simulation results are presented.

II. THE INTERACTION EFFECTS

A. NEWTON'S EXPERIMENT

When underway there are areas of increased water pressure at the bow and stern of a ship, and decreased pressure (suction) amid ships as the result of the differences in velocity of the flow of the water around the hull. When the ships are alongside each other underway, this venturi affect is increased and becomes further complicated because of the intermingling of the pressure areas of the two ships. These effects vary with the distance between ships, size, and configuration of ships, speed, depth of water and sea conditions. Changes in relative position between ships will impose rapid changes in the pressure effects on their hulls. The danger is increased if speed is reduced and radical speed changes will further aggravate the situation. In shallow waters pressure effects are more pronounced and extra care is required in maneuvering (in depths of less than twenty fathoms). It is therefore evident that to maintain station while alongside a certain amount of rudder, is usually necessary and this amount of rudder will vary with the size and load of both ships, sea and wind conditions, speed and ship separation. As a result of such increased rudder, speed is reduced which complicates the problem of maintaining stations, because it increases the handling difficulties of the ships, and it is also dangerous if a rudder casualty should occur.

The classic and original work on the reaction of vessels underway and in close proximity to one another, was the investigation carried out by the late Rear Admiral D. W. Taylor, USN [1], the results of which he presented to the Society of Naval Architects and Marine Engineers in June 1909.

The problem has been studied theoretically by Silverstein [2] and experimentally by Newton [3], with both approaches showing agreement as far as the major trends are concerned. Newton's experiments proved one important thing: It is the process of taking up or breaking away from the abeam or "fueling" position that presents the navigational risks. The experiments were conducted first with 1/50 scale models of real ships that were towed without propellers on parallel courses at different positions relative to each other longitudinally, over a range of corresponding speeds from 10 to 20 knots and at separations 50 and 100 feet, beam-to-beam.

Then full-scale trials in open sea were performed with self-propelled ships. The results of both methods were quite comparable.

When two ships pass close by on parallel courses, the pressure fields mix and the effect is to produce an unbalanced force and moment on each ship, which must be counteracted by the rudder for each to maintain course or avoid collision. Figure 1 shows the measured Y-force and N-moment acting on each model in different positions. The longitudinal separation scale shown as the abscissa is measured between the middle length of the two ships. The rudder angle data shown in Fig. 1 were the ones needed to maintain equilibrium at each of the



Figure 1. Measured Interaction Forces and Moments and Correcting Rudder Angles

Fifty-foot separation beam-to-beam.

relative positions shown. The magnitudes of the maximum forces of attraction shown in Fig. 1 are of interest. At a speed of 10 knots the maximum attraction force is 26 tons for ship A and 35 tons for ship B for the 50-feet beam-to-beam separation, and these occur when the two ships are very close to the fully abeam position 4. These forces should be quadrupled at a speed of 20 knots and according to Fig. 2 would be decreased by about 40% if the beam-to-beam separation were increased to 100 feet.



Figure 2. Variation of Interaction Forces and Moments with Transverse Separation.

Figure 3 shows the measured interaction forces and moments, and correcting rudder angles for the case of 100-feet separation.



Figure 3. Measured Interaction Forces and Moments and Correcting Rudder Angles

One hundred foot separation beam-to-beam.

It is evident from Figs. 1 and 3 that there are positions when both the interaction force and moment tend to draw one ship toward the other. Such positions are 3 for ship A and 5 for ship B. In these positions the rudder deflection angles are such that the rudder moments oppose the interaction moments. However with these deflection angles the rudder force tends to add to the force of attraction. Therefore in these positions (3 and 5), it is necessary to deflect the rudder sufficiently so that not only the interaction moment is overcome, but also a yaw angle is introduced that creates an outboard force that counteracts both the attraction and the rudder force. By these means the two ships should be able to avoid collision in positions 3 and 5, provided there is enough transverse separation between the two ships so that the available rudder force can correct the inward swing caused by the interaction moment.

It should be noted that position 3 immediately precedes, and position 5 immediately follows the directly abeam position when the two ships have to apply opposite rudder to keep on parallel courses. Thus in the short space of time between positions 3 and 4 for ship A and between positions 4 and 5 for ship B, the rudder has to swing from a large port deflection to a starboard deflection. Obviously the precise timing when this has to be done is not easy to choose. It is therefore true that the two ships suffer the greatest risk of collision in positions 3 and 5, which would be augmented if the seas were rough and a heavy wind were blowing.

III. EQUATIONS OF MOTION

A. THE GENERAL CASE

It is clear that bodies moving in a fluid medium are free to move with six degrees of freedom. In order to define the equations of motion, a right-hand rectangular coordinate system is established, the origin of which is chosen to be in the body itself, as shown in Fig. 4. The origin could very well be at the center of gravity but for generalizing the problem, it can be placed anywhere else. The origin and the axes are fixed with respect to the body but movable with respect to the axes fixed in space. It is assumed that at t=0 the two systems coincide



CG: Center of Gravity

Figure 4. The Coordinates System.

The motion of a rigid body is expressed by Newton's Laws of motion in vector form:

$$\vec{F}(\text{External Force}) = \frac{d}{dt}[\text{Momentum}]$$
$$\vec{M}(\text{External Moment}) = \frac{d}{dt}[\text{Angular Momentum}] \tag{3.1}$$

Then the six equations (six degrees of freedom) describing the ship's motion have been found [4] to be:

$$\begin{aligned}
X &= m[\dot{U}-RV+QW-X_G(R^2+Q^2) + Y_G(PQ-\dot{R}) + Z_G(PR+\dot{Q})] \\
Y &= m[\dot{V}-PW+RU+X_G(\dot{R}+PW) - Y_G(P^2+R^2) + Z_G(PQ-\dot{P})] \\
Z &= m[\dot{W}-QU+PV+X_G(PR-\dot{Q}) + Y_G(\dot{P}+QR) - Z_G(Q^2+P^2)] \\
L &= \dot{P}I_X + (I_Z-I_y)QR + m[Y_G(\dot{W}-QU+PV)-Z_G(\dot{V}-PW+RU)] \\
M &= \dot{Q}I_y + (I_x-I_Z)PR + m[Z_G(\dot{U}-RV+QW) - X_G(\dot{W}-QU+PV)] \\
N &= \dot{R}I_Z + (I_y-I_x)PQ + m[X_G(\dot{V}-PW+RU) - Y_G(\dot{U}-RV+QW)]
\end{aligned} \tag{3.2}$$

satisfying equations --

$$\begin{aligned}
\vec{F} &= \vec{i}\cdot X + \vec{j}\cdot Y + \vec{K}\cdot Z \\
\vec{M} &= \vec{i}\cdot L + \vec{j}\cdot M + \vec{K}\cdot N
\end{aligned} \tag{3.3}$$

and where

- m - mass of the ship
- X,Y,Z - components of force in the X,Y,Z directions
- L,M,N - components of applied moment about the X,Y,Z axes
- U,V,W - components of velocity in the X,Y,Z directions
- X_G,Y_G,Z_G - distances of origin from center of gravity in the X,Y,Z directions
- P,Q,R - components of angular velocity about the X,Y,Z axes
- I_x,I_y,I_z - moments of inertia about the X,Y,Z axes

Equations (3.2) describe the reaction of the rigid body to applied forces as a function of the geometric and physical characteristics of the body itself. They do not include any of the applied external forces such as propeller thrust, or rudder forces, or forces and moments due to the fins (if they exist). They do not include the reaction forces of the fluid (hydrodynamic forces) nor do they include the waves and wind forces. The reactions of the rigid body (ship) are characteristic and must be considered in studying control problems.

B. THE HORIZONTAL PLANE MOTION

It is clear that the ship's motion in calm waters is described only by the following three equations:

$$X = m[\dot{U}-RV+QW-X_G(R^2+Q^2) + Y_G(PQ-\dot{R}) + Z_G(PR+\dot{Q})] \quad \text{(surge)}$$

$$Y = m[\dot{V}+UR-PW+X_G(\dot{R}+PW) - Y_G(P^2+R^2) + Z_G(RQ-\dot{P})] \quad \text{(sway)}$$

$$N = \dot{R}I_z + (I_y-I_x)PQ + m[X_G(\dot{V}-PW+RU) - Y_G(\dot{U}-RV+QW)] \quad \text{(yaw)} \qquad (3.4)$$

Under the assumption of calm water conditions it is true that Roll=Pitch=Heave = 0, and the three equations of motion are the so-called horizontal plane equations. Therefore since horizontal plane motion implies: $P= \dot{P}= Q= \dot{Q}= W= \dot{W}= 0$ equations (3.4) can be written as follows:

$$X = m[\dot{U}-RV-X_G R^2-Y_G\dot{R}]$$

$$Y = m[\dot{V}+UR+X_G\dot{R}-Y_G R^2] \qquad (3.5)$$

$$N = \dot{R}I_z+m[X_G(\dot{V}+RU)-Y_G(\dot{U}-RV)]$$

Assuming that the coordinate's origin is placed on the center of gravity of the ship, then $X_G = Y_G = 0$ and Eqs. (3.5) become:

$$\begin{aligned} X &= m[\dot{U}-RV] \\ Y &= m[\dot{V}+UR] \\ N &= \dot{R}I_z \end{aligned} \tag{3.6}$$

Defining:

Ψ_T = Yaw angle

and substituting the relations $R = \dot{\Psi}_T$ and $\dot{R} = \ddot{\Psi}_T$ into (3.6) yields:

$$\begin{aligned} X &= m[\dot{U}-\dot{\Psi}_T V] \\ Y &= m[\dot{V}+U\dot{\Psi}_T] \\ N &= \ddot{\Psi}_T I_z \end{aligned} \tag{3.7}$$

1. Linearization of the Horizontal Plane Equations

An equilibrium condition is one of a steady forward motion of the ship for which U_0 = Constant, $V_0 = 0$, Ψ_0 = Constant. Then considering small perturbations u,v,Ψ;

$U = U_0 + u$

$$V = V_0 + v$$

$$\Psi_T = \Psi_0 + \Psi$$

$$R = R_0 + r$$

The right-hand parts of Eqs. (3.7) take the form:

$$\dot{V} + U\dot{\Psi}_T = \dot{V}_0 + \dot{v} + (U_0+u)(\dot{\Psi}_0+\dot{\Psi})$$

But $\dot{V}_0 = \dot{\Psi}_0 = 0$, and dropping second-order terms yields:

$$\dot{V} + U\dot{\Psi}_T = \dot{v} + U_0.\dot{\Psi}$$

And since $V_0 = 0$, Eqs. (3.7) becomes:

$$\begin{aligned} X &= m\dot{u} \\ Y &= m[\dot{v}+\Psi U_0] \\ N &= I_z \cdot \ddot{\Psi} \end{aligned} \tag{3.8}$$

Then setting again $\dot{\Psi} = r$ and $\ddot{\Psi} = \dot{r}$ gives

$$\begin{aligned} X &= m\dot{u} \\ Y &= m[\dot{v}+r \cdot U_0] \\ N &= I_z \cdot \dot{r} \end{aligned} \tag{3.9}$$

The hydrodynamic forces and moment for these particular motions have been found [5].

$$\begin{aligned} X &= \frac{\partial X}{\partial u} \cdot \Delta u + \frac{\partial X}{\partial \dot{u}} \cdot \dot{u} = X_u \cdot \Delta u + X_{\dot{u}} \cdot \dot{u} \\ Y &= \frac{\partial Y}{\partial v} \cdot v + \frac{\partial Y}{\partial \dot{v}} \dot{v} + \frac{\partial Y}{\partial r} \cdot r + \frac{\partial Y}{\partial \dot{r}} \dot{r} = Y_v \cdot v + Y_{\dot{v}} \cdot \dot{v} + Y_r \cdot r + Y_{\dot{r}} \cdot \dot{r} \\ N &= \frac{\partial N}{\partial v} \cdot v + \frac{\partial N}{\partial \dot{v}} \dot{v} + \frac{\partial N}{\partial r} \cdot r + \frac{\partial N}{\partial \dot{r}} \dot{r} = N_v \cdot v + N_{\dot{v}} \cdot \dot{v} + N_r \cdot r + N_{\dot{r}} \cdot \dot{r} \end{aligned} \tag{3.10}$$

The cross-coupled derivatives Y_r, $Y_{\dot{r}}$, N_v, $N_{\dot{v}}$, even though they have small nonzero values, have to be included unless the ship under consideration is symmetrical about the YZ-plane, which is not usually the case. Thus taking into account the hydrodynamic derivatives Eqs. (3.9) become:

$$\begin{aligned} 0 &= -X_u(u-U_0) + (m-X_{\dot{u}})\dot{u} \\ 0 &= -Y_v \cdot v + (m-Y_{\dot{v}})\dot{v} - (Y_r - mU_0)r - Y_{\dot{r}} \cdot \dot{r} \\ 0 &= -N_v \cdot v - N_{\dot{v}} \cdot \dot{v} - N_r \cdot r + (I_z - N_{\dot{r}})\dot{r} \end{aligned} \tag{3.11}$$

2. Nondimensionalization of the Horizontal Plane Equations

For several reasons and mainly for computer simulation purposes, it is necessary to nondimensionalize equations (3.11). Table I gives dimensionalized and nondimensionalized quantities and their conversion relations. The prime symbol indicates the nondimensional form of each quantity.

In equations (3.11) the force equations are divided through by $\frac{\rho}{2} L^2V^2$ and the moment equation by $\frac{\rho}{2} L^3V^2$ yielding

$$
\begin{aligned}
0 &= -Y'_v \cdot v' + (m' - Y'_{\dot{v}})\dot{v}' - (Y'_r - m' \cdot U'_0)r' - Y'_{\dot{r}} \cdot \dot{r}' \\
0 &= -N'_v \cdot v' - N'_{\dot{v}} \cdot \dot{v}' - N'_r \cdot r' + (I'_z - N'_{\dot{r}})\dot{r}' \qquad (3.12) \\
0 &= -X'_u(u' - U'_0) + (m' - X'_{\dot{u}})\dot{u}'
\end{aligned}
$$

If the motion of the ship is to be considered under external perturbations and with controls working, equations (3.12) must include terms expressing forces and moments due to sea and wind excitations (in rough weather), and forces and moments caused by rudder deflections or movable fin deflections. The rudder and fins forces and moments are considered control elements. The rest of the forces and moments are not normally controlled inputs, but they must be included in cases where the ship has to be controlled in their presence. In this last category, belong the interactive forces and moments generated in the cases of ships in close underway replenishment stations.

Considering only rudder control inputs, equations (3.12) become

TABLE I

NONDIMENSIONALIZATION RELATIONS

m	m'	$m' = m/\frac{\rho}{2} L^3$
u	u'	$u' = u/V$
v	v'	$v' = v/V$
$\dot{u}$	$\dot{u}'$	$\dot{u}' = \dot{u}L/V^2$
$\dot{v}$	$\dot{v}'$	$\dot{v}' = \dot{v}L/V^2$
I_z	I_z'	$I_z' = m/\frac{\rho}{2} L^5$
r	r'	$r' = rL/V$
$\dot{r}$	$\dot{r}'$	$\dot{r}' = \dot{r}L^2/V^2$
X_u	X_u'	$X_u' = X_u/\frac{\rho}{2} L^2V$
$X_{\dot{u}}$	$X_{\dot{u}}'$	$X_{\dot{u}}' = X\dot{u}/\frac{\rho}{2} L^3$
Y_v	Y_v'	$Y_v' = Y_v/\frac{\rho}{2} L^2V$
Y_r	Y_r'	$Y_r' = Y_r/\frac{\rho}{2} L^3V$
$Y_{\dot{v}}$	$Y_{\dot{v}}'$	$Y_{\dot{v}}' = Y_{\dot{v}}/\frac{\rho}{2} L^3$
$Y_{\dot{r}}$	$Y_{\dot{r}}'$	$Y_{\dot{r}}' = Y_{\dot{r}}/\frac{\rho}{2} L^4$
N_v	N_v'	$N_v' = N_v/\frac{\rho}{2} L^3V$
$N_{\dot{v}}$	$N_{\dot{v}}'$	$N_{\dot{v}}' = N_{\dot{v}}/\frac{\rho}{2} L^4$
N_r	N_r'	$N_r' = N_r/\frac{\rho}{2} L^4V$
$N_{\dot{r}}$	$N_{\dot{r}}'$	$N_{\dot{r}}' = N_{\dot{r}}/\frac{\rho}{2} L^5$
$N_v \cdot v$	$N_v' \cdot v'$	$N_v' \cdot v' = N_v \cdot v/\frac{\rho}{2} L^3V^2$
$N_{\dot{v}} \cdot \dot{v}$	$N_{\dot{v}}' \cdot \dot{v}'$	$N_{\dot{v}}' \cdot \dot{v}' = N_{\dot{v}} \cdot \dot{v}/\frac{\rho}{2} L^3V^2$

ρ = Sea water density in lb/ft^3

L = Length of ship in ft.

V = Speed of ship in ft/sec.

$$-Y'_v \cdot v' + (m'-Y'_{\dot{v}})\dot{v}' - (Y'_r - m'U'_0)r' - Y'_{\dot{r}}\dot{r}' = Y'_\delta \cdot \delta \quad \text{(Sway)}$$

$$-N'_v \cdot v' - N'_{\dot{v}} \cdot \dot{v}' - N'_r \cdot r' + (I'_z - N'_{\dot{r}})\dot{r}' = N'_\delta \cdot \delta \quad \text{(Yaw)}$$

$$-X'_u \cdot (u'-U'_0) + (m'-X'_{\dot{u}})\dot{u}' = X'_\delta \cdot \delta \quad \text{(Surge)} \tag{3.13}$$

where, δ = Rudder-deflection angle, measured from the XZ-plane of the ship to the plane of the rudder; positive deflection corresponds to a turn to port for rudder(s) located at stern.

Y'_δ, N'_δ, X'_δ = nondimensionalized forms of the rudder forces and moment,

$Y_\delta = \frac{\partial Y}{\partial \delta}$, $N\delta = \frac{\partial N}{\partial \delta}$, $X\delta = \frac{\partial X}{\partial \delta}$, respectively.

3. Manipulation of the Equations for Computer Simulation

Equations (3.13) can be written as follows:

$$v'(s)[s(m'-Y'_{\dot{v}}) - Y'_v] + r'(s)[-sY'_{\dot{r}} + (m'U'_0 - Y'_r)] = Y'_\delta \cdot \delta(s)$$

$$v'(s)[-s \cdot N'_{\dot{v}} - N'_v] + r'(s)[s(I_z - N'_{\dot{r}}) - N'_r] = N'_\delta \cdot \delta(s)$$

$$u'(s)[s(m'-X\dot{u}')] + u'(s)[-X_u] + X'_u \cdot \frac{U'_0}{s} = X'_\delta \cdot \delta(s) \tag{3.14}$$

or

$$\frac{v'(s)}{s}[s^2(m'-Y'_{\dot{v}}) - sY'_v] + \Psi'(s)[-s^2 Y'_{\dot{r}} + s(m'U'_0 - Y'_r)] = Y'_\delta \cdot \delta(s)$$

$$\frac{v'(s)}{s}[-s^2 N'_{\dot{v}} - sN'_v] + \Psi'(s)[s^2(I'_z - N'_{\dot{r}}) - sN'_r] = N'_\delta \cdot \delta(s)$$

$$\frac{u'(s)}{s}[s^2(m'-X'_{\dot{u}}) - sX'_u] + X'_u \cdot \frac{U'_0}{s} = X'_\delta \cdot \delta(s) \tag{3.15}$$

or

$$\frac{v'(s)}{s}\,[\alpha_{aA}s^2+\beta_{aA}s+\gamma_{aA}] + \Psi'(s)\,[\alpha_{bA}s^2+\beta_{bA}s+\gamma_{bA}] = Y'_{\delta}\cdot\delta(s)$$

$$\frac{v'(s)}{s}\,[\alpha_{aB}s^2+\beta_{aB}s+\gamma_{aB}] + \Psi'(s)\,[\alpha_{bB}s^2+\beta_{bB}s+\gamma_{bB}] = N'_{\delta}\cdot\delta(s)$$

$$\frac{u'(s)}{s}\,[\alpha_{cC}s^2+\beta_{cC}s+\gamma_{cC}] = X'_{\delta}\cdot\delta(s) - X'_{u}\cdot\frac{U'_0}{s} \qquad (3.16)$$

where

$$\alpha_{aA} = m' - Y'_{\dot{v}}$$

$$\beta_{aA} = -Y'_{v}$$

$$\gamma_{aA} = 0$$

$$\alpha_{bA} = Y'_{\dot{r}}$$

$$\beta_{bA} = m'\cdot U'_0 - Y'_{r}$$

$$\gamma_{bA} = 0$$

$$\alpha_{aB} = N'_{\dot{v}}$$

$$\beta_{aB} = -N'_{v}$$

$$\gamma_{aB} = 0$$

$$\alpha_{bB} = (I'_z - N'_{\dot{r}})$$

$$\beta_{bB} = -N'_{r}$$

$$\gamma_{bB} = 0$$

$$\alpha_{cC} = m' - X'_{\dot{u}}$$

$$\beta_{cC} = -X'_{u}$$

$$\gamma_{cC} = 0$$

Setting

$$\frac{v'(s)}{s} = A(s) \quad \text{or} \quad v' = \dot{A}$$

$$\psi'(s) = B(s) \quad \text{or} \quad \psi = B$$

$$\frac{u'(s)}{s} = C(s) \quad \text{or} \quad u' = \dot{C}$$

and

$$IF1 = Y\delta' \cdot \delta(s) = KA1 * D1$$

$$IF2 = N\delta' \cdot \delta(s) = KB1 * D1$$

$$IF3 = X\delta' \cdot \delta(s) - X'_u \cdot \frac{U'_0}{s} = KC1 * D1 - X'_u \cdot U'_o$$

equations (3.16) can be written as follows:

$$\alpha_{aA}\ddot{A} + \beta_{aA}\dot{A} + \gamma_{aA}A + \alpha_{bA}\ddot{B} + \beta_{bA}\dot{B} + \gamma_{bA} \cdot B = IF1$$

$$\alpha_{aB}\ddot{A} + \beta_{aB}\dot{A} + \gamma_{aB}A + \alpha_{bB}\ddot{B} + \beta_{bB}\dot{B} + \gamma_{bB} \cdot B = IF2 \qquad (3.17)$$

$$\alpha_{cC} \cdot \ddot{C} + \beta_{cC}\dot{C} + \gamma_{cC}C = IF3$$

or

$$\alpha_{aA}\ddot{A} + \alpha_{bA} \cdot \ddot{B} = I1$$

$$\alpha_{aB}\ddot{A} + \alpha_{bB} \cdot \ddot{B} = I2 \qquad (3.18)$$

$$\alpha_{cC}\ddot{C} = I3$$

where

$$I1 = -\beta_{aA}\dot{A} - \gamma_{aA}A - \beta_{bA}\dot{B} - \gamma_{bA}B + IF1$$

$$I2 = -\beta_{aB}\dot{A} - \gamma_{aB}A - \beta_{bB}\dot{B} - \gamma_{bB}B + IF2$$

$$I3 = -\beta_{cC}\dot{C} - \gamma_{cC}C + IF3$$

and solving for $\ddot{A}$, $\ddot{B}$, $\ddot{C}$, yields

$$\ddot{A} = \frac{\begin{vmatrix} I_1 & \alpha_{bA} & 0 \\ I_2 & \alpha_{bB} & 0 \\ I_3 & 0 & \alpha_{cC} \end{vmatrix}}{[\Delta]}, \quad \ddot{B} = \frac{\begin{vmatrix} \alpha_{aA} & I_1 & 0 \\ \alpha_{aB} & I_2 & 0 \\ 0 & I_3 & \alpha_{cC} \end{vmatrix}}{[\Delta]}, \quad \ddot{C} = \frac{\begin{vmatrix} \alpha_{aA} & \alpha_{bA} & I_1 \\ \alpha_{aB} & \alpha_{bB} & I_2 \\ 0 & 0 & I_3 \end{vmatrix}}{[\Delta]} \tag{3.19a}$$

where

$$\Delta = \begin{vmatrix} \alpha_{aA} & \alpha_{bA} & 0 \\ \alpha_{aB} & \alpha_{bB} & 0 \\ 0 & 0 & \alpha_{cC} \end{vmatrix}$$

and furthermore solving for v', u', Ψ' yields

$$\begin{aligned} v' &= \dot{A} = v'_0 + \int \ddot{A}\, dt \\ \Psi' &= \Psi_0 + \int \dot{B}\, dt = \Psi_0 + \int [\dot{B}_0 + \int \ddot{B} dt] dt \\ u' &= \dot{C} = u'_0 + \int \ddot{C}\, dt \end{aligned} \tag{3.19b}$$

Then according to Figure 5 [4]:

$$\begin{aligned} \dot{y}' &= u' \sin\Psi + v' \cos\Psi \\ \dot{x}' &= u' \cos\Psi - v' \sin\Psi \end{aligned} \tag{3.19c}$$

Thus giving

$$y' = y'_0 + \int \dot{y}' dt \quad \text{and} \quad x' = x'_0 + \int \dot{x}' dt \tag{3.19d}$$

Equations (3.19) form the basis of CSMP computer program I. This program was simulated for a ship in motion with a speed $U'_0 = \frac{U_0}{V} = 1.0$ and a constant rudder deflection δ = D1 = 0.1 rad. The results are shown in Figures 6 and 7. Figure 6 is



Figure 5. The Horizontal Plane Motions.

a Yaw versus Time plot, and Figure 7 is the turning radius (sway versus surge) characteristic of the ship.

This ship is a class D surface ship and its hydrodynamic coefficients[1] given in Table II were used in the computer simulation, and will be considered in all further work throughout this thesis.

4. Stability Investigation

The test for stability is to establish an equilibrium situation and determine whether the system returns to the

---

[1] Courtesy of Dr. Grant Hagen, David Taylor Model Basin.



Figure 6. Yaw vs. Time



Figure 7. The Turning Radius.

original condition of equilibrium after an infinitesimal disturbance. If it returns to the original equilibrium condition, after the disturbance is removed, it is stable. If it departs or has the tendency to depart, it is unstable.

For the ship, such an equilibrium condition is the one of a straight ahead motion at constant speed. A ship which is dynamically unstable, cannot maintain straight line motion

TABLE II

NONDIMENSIONALIZED COEFFICIENTS FOR THE CLASS D SHIP

m'	0.0045
I_z'	0.0003
N_r'	-0.0012
$N_{\dot{r}}'$	-0.0002
N_v'	-0.0012
$N_{\dot{v}}'$	-0.0001
N_δ'	-0.00084
Y_r'	0.004
$Y_{\dot{r}}'$	-0.0002
Y_v'	-0.0063
$Y_{\dot{v}}'$	-0.0025
Y_δ'	0.0019
X_u'	-0.0019
$X_{\dot{u}}'$	-0.0036
X_δ'	-0.0011

when there is no rudder deflection. The behavior of the ship (plant) is to be examined under the influence of forcing functions (disturbances), with controls (rudders) fixed ($\delta = 0$), or under the influence of controls acting as disturbances.

With controls fixed and for $U_0' = 1.0$ Eqs. (3.16) become:

$$\frac{v'(s)}{s}[\alpha_{aA}s^2+\beta_{aB}s] + \Psi'(s)[\alpha_{bA}s^2+\beta_{bA}s] = 0$$

$$\frac{v'(s)}{s}[\alpha_{aB}s^2+\beta_{aB}s] + \Psi'(s)[\alpha_{bB}s^2+\beta_{bB}s] = 0 \qquad (3.20)$$

$$\frac{u'(s)}{s}[\alpha_{cC}s^2+\beta_{cC}s] = -Xu'$$

Since a steady forward motion, $\Delta u' = 0$, has been assumed, then the surge equation can be neglected giving:

$$\frac{v'(s)}{s}[\alpha_{aA}s^2+\beta_{aB}s] + \Psi'(s)[\alpha_{bA}s^2+\beta_{bA}s] = 0$$

$$\qquad (3.21)$$

$$\frac{v'(s)}{s}[\alpha_{aB}s^2+\beta_{aB}s] + \Psi'(s)[\alpha_{bB}s^2+\beta_{bB}s] = 0$$

or

$$v'(s)[\alpha_{aA}s+\beta_{aA}] + r'(s)[\alpha_{bA}s+\beta_{bA}] = 0$$

$$\qquad (3.22)$$

$$v'(s)[\alpha_{aB}s+\beta_{aB}] + r'(s)[\alpha_{bB}s+\beta_{bB}] = 0$$

The characteristic equation is:

$$[(\alpha_{aA}\cdot\alpha_{bB}-\alpha_{aB}\alpha_{bA})s^2+(\alpha_{bB}\beta_{aA}+\alpha_{aA}\beta_{bB}-\alpha_{aB}\beta_{bA}-\alpha_{bA}\beta_{aB})s+(\beta_{aA}\beta_{bB}-\beta_{aB}\beta_{bA})] = 0$$

or

$$c_1s^2 + c_2s + c_3 = 0 \qquad (3.23)$$

where

$$c_1 = \alpha_{aA}\alpha_{bB} - \alpha_{aB}\alpha_{bA}$$

$$c_2 = \alpha_{bB}\beta_{aA} + \alpha_{aA}\beta_{bB} - \alpha_{aB}\beta_{bA} - \alpha_{bA}\beta_{aB}$$

$$c_3 = \beta_{aA}\beta_{bB} - \beta_{aB}\beta_{bA}$$

The roots of the characteristic equation are

$$\rho_{1,2} = \frac{-c_2 \pm \sqrt{c_2^2 - 4c_1c_3}}{2c_1} = \frac{-c_2/c_1 \pm [[c_2/c_1]^2 - 4c_3/c_1]^{1/2}}{2}$$

For stability it is necessary that $\rho_1<0$ and $\rho_2<0$, which is guaranteed when

$$\beta = \frac{c_2}{c_1} > 0 \quad \text{and} \quad \gamma = \frac{c_3}{c_1} > 0$$

That is the condition for stability is given as:

$$\beta > 0 \quad \text{and} \quad \gamma > 0. \tag{3.24}$$

For the class D surface ship implementing values of Table II gives:

$$\alpha_{aA} = 0.007$$
$$\beta_{aA} = 0.0063$$
$$\alpha_{bA} = 0.0002$$
$$\beta_{bA} = 0.0005$$
$$\alpha_{aB} = 0.0001$$
$$\beta_{aB} = 0.0012$$
$$\alpha_{bB} = 0.0005$$
$$\beta_{bB} = 0.0012$$
$$\alpha_{cC} = 0.00486$$
$$\beta_{cC} = 0.0012$$

And further substitution gives:

$$\beta = 3.227 > 0, \quad \gamma = 2.0 > 0$$

It is therefore proved that this particular ship possesses controls fixed stability.

5. The Transfer Functions

For $U_0' = 1.0$ Eqs. (3.16) can be written again:

$$\frac{v'(s)}{s}\cdot K_{aA} + \Psi'(s)\cdot K_{bA} + \frac{u'(s)}{s}\cdot(0) = Y'_\delta\cdot\delta(s)$$

$$\frac{v'(s)}{s}\cdot K_{aB} + \Psi'(s)\cdot K_{bB} + \frac{u'(s)}{s}\cdot(0) = N'_\delta\cdot\delta(s) \qquad (3.25)$$

$$\frac{v'(s)}{s}\cdot 0 + \Psi'(s)(0) + \frac{u'(s)}{s}\cdot K_{cC} = X'_\delta\cdot\delta(s) - Xu'\cdot\frac{1}{s}$$

where

$$K_{aA} = \alpha_{aA}s^2 + \beta_{aA}s$$

$$K_{bA} = \alpha_{bA}s^2 + \beta_{bA}s$$

$$K_{aB} = \alpha_{aB}s^2 + \beta_{aB}s$$

$$K_{bB} = \alpha_{bB}s^2 + \beta_{bB}s$$

$$K_{cC} = \alpha_{cC}s^2 + \beta_{cC}s$$

Then solving Eqs. (3.25) yields

$$\frac{v'(s)}{s}/\delta(s) = \frac{\begin{vmatrix} Y'_\delta & K_{bA} & 0 \\ N'_\delta & K_{bB} & 0 \\ X'_\delta & 0 & K_{cC} \end{vmatrix}}{[\Delta]} = \frac{[N_1]}{[\Delta]}, \quad \Psi'(s)/\delta(s) = \frac{\begin{vmatrix} K_{aA} & Y'_\delta & 0 \\ K_{aB} & N'_\delta & 0 \\ 0 & X'_\delta & K_{cC} \end{vmatrix}}{[\Delta]} = \frac{[N_2]}{[\Delta]},$$

$$\frac{u'(s)}{s}/\delta(s) = \frac{\begin{vmatrix} K_{aA} & K_{bA} & Y'_\delta \\ K_{aB} & K_{bB} & N'_\delta \\ 0 & 0 & X'_\delta \end{vmatrix}}{[\Delta]} = \frac{[N_3]}{[\Delta]} \qquad (3.26)$$

where

$$\Delta = \begin{vmatrix} K_{aA} & K_{bA} & 0 \\ K_{aB} & K_{bB} & 0 \\ 0 & 0 & K_{cC} \end{vmatrix}$$

or

$$\Delta = K_{aA} \cdot K_{bB} K_{cC} - K_{aB} K_{bA} K_{cC} = K_{cC} \cdot [K_{aA} K_{bB} - K_{aB} K_{bA}]$$

or

$$\Delta = s(\alpha_{cC}s+\beta_{cC})[s(\alpha_{aA}s+\beta_{aA})s(\alpha_{bB}s+\beta_{bB}) - s(\alpha_{aB}s+\beta_{aB})s(\alpha_{bA}s+\beta_{bA})$$

and finally

$$\Delta = s^3(\alpha_{cC}s+\beta_{cC})[\alpha_{aA} \cdot \alpha_{bB} - \alpha_{aB}\alpha_{bA})s^2 + (\alpha_{aA}\beta_{bB} + \alpha_{bB}\beta_{aA} - \alpha_{aB}\beta_{bA} - \beta_{aB}\alpha_{bA})s + (\beta_{aA}\beta_{bB} - \beta_{aB}\beta_{bA})]$$

Evaluating N_1, N_2, and N_3 and substituting into Eqs. (3.26) yields:

$$\frac{v'(s)}{\delta(s)} = \frac{K_v(s+z_v)}{s^2+\beta s+\gamma} \tag{3.27}$$

$$\frac{\psi'(s)}{\delta(s)} = \frac{K_r(s+z_r)}{s(s^2+\beta s+\gamma)} \tag{3.28}$$

$$\frac{u'(s)}{\delta(s)} = \frac{K_u}{s+p_u} \tag{3.29}$$

where

$$
\begin{aligned}
K_v &= \frac{Y'_\delta\,\alpha_{bB} - N'_\delta\,\alpha_{bA}}{\alpha_{aA}\alpha_{bB} - \alpha_{aB}\alpha_{bA}} \\
Z_v &= \frac{Y'_\delta\,\beta_{bB} - N'_\delta\,\beta_{bA}}{Y'_\delta\,\alpha_{bB} - N'_\delta\,\alpha_{bA}} \\
K_r &= \frac{N'_\delta\,\alpha_{aA} - Y'_\delta\,\alpha_{aB}}{\alpha_{aA}\alpha_{bB} - \alpha_{aB}\alpha_{bA}} \\
Z_r &= \frac{N'_\delta\,\beta_{aA} - Y'_\delta\,\beta_{aB}}{N'_\delta\,\alpha_{aA} - Y'_\delta\,\alpha_{aB}} \qquad (3.30) \\
K_u &= \frac{X\delta'}{\alpha_{cC}} \\
P_u &= \frac{\beta_{cC}}{\alpha_{cC}} \\
\beta &= \frac{\alpha_{aB}\beta_{bB} + \alpha_{bB}\beta_{aA} - \alpha_{aB}\beta_{bA} - \beta_{aB}\alpha_{bA}}{\alpha_{aA}\alpha_{bB} - \alpha_{aB}\alpha_{bA}} \\
\gamma &= \frac{\beta_{aA}\beta_{bB} - \beta_{aB}\beta_{bA}}{\alpha_{aA}\alpha_{bB} - \alpha_{aB}\alpha_{bA}}
\end{aligned}
$$

The transfer function determination leads now to the block diagram representation of the plant (ship) shown in Fig. 8, where the rudder deflection is taken as the only control input.



Figure 8. The Open Loop System

IV. THE CONTROL LOOPS

The replenishment at sea operation as a control problem is directly dependent on the operational responsibilities of each of the ships involved in it. It has already been stated that the replenishing ship is responsible for course keeping only, and that the receiving ship is responsible for course and station keeping. Hence from a control point of view it is clear that two different control loops should be required, namely, the course keeping loop and the distance (station) keeping loop.

A. PATHKEEPING LOOP

1. The Block Diagram

The control loop is shown in Figure 9. For a course keeping action the important output variables of the control system should be the yaw, Ψ', and the yaw rate, $\dot{\Psi}'$. Since the main objective is course keeping and not course changing, the control loop should include no input yaw reference. It includes the existing time lag t_r between the helm's action and the desired actual displacement of the rudder itself. Non-dimensionalized, the time lag t_r' is usually taken equal to 0.1.

2. Determination of K and K_t for a Desired Performance.

The proper values for K and K_t are to be determined for a critically damped response of the loop and therefore for a desired performance of the system dictated by the condition: $\zeta = 1.0$.



δ_d - Ordered Rudder angle (helm)

δ - Actual Rudder angle

t_r' - Nondimensional time lag ($\simeq 0.1$)

Figure 9. The Course Keeping Loop.

A computer program called PARAM "A" implemented accordingly will yield a set of pairs of values of K and K_t for any desired ζ for a range of operating frequencies.

The equivalent of the controlled loop of Fig. 9 is shown in Fig. 10. Then comparison of Figs. 10 and 11 gives:

$$G = \frac{10K_r(s+z_r)}{s(s+10)(s^2+\beta s+\gamma)}, \quad H = K + K_t \cdot s$$

The overall closed loop transfer function is

$$\frac{G}{1-GH} = \frac{\dfrac{10K_r(s+z_r)}{s(s+10)(s^2+\beta s+\gamma)}}{1 - \dfrac{10K_r(s+z_r)(K_t s+K)}{s(s+10)(s^2+\beta s+\gamma)}}$$

and the characteristic equation is

$$s(s+10)(s^2+\beta s+\gamma) - 10K_r(s+z_r)(K_t s+K) = 0$$



Figure 10. The Equivalent Loop.



Figure 11. General Feedback Control Loop.

Or

$$s^4+(10+\beta)s^3+[(10\beta+\gamma)-10K_rK_t]s^2+[10\gamma-10K_rK-10K_rZ_rK_t]s-10K_rZ_rK = 0 \qquad (4.1)$$

Considering again the Class D surface ship and evaluating Eqs. (3.30) according to the values of Table II for the required quantities

$$Kr = -1.74425$$

$$Zr = 1.24744$$

$$\beta = 3.227$$

$$\gamma = 2.0$$

And now Eq. (4.1) becomes:

$$s^4+13.2227s^3+[34.27-17.4425K_t]s^2+[20.0+17.4425K+21.7584K_t]s + 21.7584K = 0 \qquad (4.2)$$

The aforementioned PARAM "A" computer program was simulated for the case of Eq. (4.2) and for $\zeta = 1.0$ and a sample of the computer result containing the permissible pairs of values of K and K_t is given in Table III.

3. Computer Simulation of the Controlled Plant

From Fig. 9 the relation between δ and δd is

$$\delta = \frac{10}{s+10}\,\delta d \quad \text{and} \quad \delta d = (K_t s+K)\Psi'$$

Therefore:

$$\delta = \frac{10}{s+10}(K_t S+K)\Psi' \qquad (4.3)$$

TABLE III

APPROPRIATE VALUES OF PARAMETERS K AND K_t

K	K_t	Ω	ζ	Third Parameter
0.80689E-01	-0.38959E 00	0.29719E 00	0.10000E 01	0.13665E 08
0.84989E-01	-0.37530E 00	0.30447E 00	0.10000E 01	0.13665E 08
0.89534E-01	-0.36055E 00	0.31193E 00	0.10000E 01	0.13665E 08
0.94340E-01	-0.34533E 00	0.31957E 00	0.10000E 01	0.13665E 08
0.99424E-01	-0.32961E 00	0.32740E 00	0.10000E 01	0.13665E 08
0.10481E 00	-0.31338E 00	0.33542E 00	0.10000E 01	0.13665E 08
0.11050E 00	-0.29659E 00	0.34364E 00	0.10000E 01	0.13665E 08
0.11654E 00	-0.27924E 00	0.35206E 00	0.10000E 01	0.13665E 08
0.12294E 00	-0.26129E 00	0.36068E 00	0.10000E 01	0.13665E 08
0.12973E 00	-0.24270E 00	0.36952E 00	0.10000E 01	0.13665E 08
0.13693E 00	-0.22344E 00	0.37857E 00	0.10000E 01	0.13665E 08
0.14458E 00	-0.20348E 00	0.38785E 00	0.10000E 01	0.13665E 08
0.15271E 00	-0.18277E 00	0.39735E 00	0.10000E 01	0.13665E 08
0.16136E 00	-0.16127E 00	0.40709E 00	0.10000E 01	0.13665E 08
0.17056E 00	-0.13893E 00	0.41706E 00	0.10000E 01	0.13665E 08
0.18037E 00	-0.11569E 00	0.42728E 00	0.10000E 01	0.13665E 08
0.19084E 00	-0.91504E-01	0.43775E 00	0.10000E 01	0.13665E 08
0.20201E 00	-0.66294E-01	0.44847E 00	0.10000E 01	0.13665E 08
0.21395E 00	-0.39992E-01	0.45946E 00	0.10000E 01	0.13665E 08
0.22673E 00	-0.12515E-01	0.47072E 00	0.10000E 01	0.13665E 08
0.24042E 00	0.16227E-01	0.48225E 00	0.10000E 01	0.13665E 08
0.25512E 00	0.46335E-01	0.49406E 00	0.10000E 01	0.13665E 08
0.27092E 00	0.77921E-01	0.50617E 00	0.10000E 01	0.13665E 08
0.28793E 00	0.11112E 00	0.51857E 00	0.10000E 01	0.13665E 08
0.30628E 00	0.14608E 00	0.53127E 00	0.10000E 01	0.13665E 08
0.32611E 00	0.18295E 00	0.54429E 00	0.10000E 01	0.13665E 08
0.34759E 00	0.22194E 00	0.55762E 00	0.10000E 01	0.13665E 08
0.37092E 00	0.26326E 00	0.57129E 00	0.10000E 01	0.13665E 08
0.39630E 00	0.30716E 00	0.58528E 00	0.10000E 01	0.13665E 08
0.42402E 00	0.35392E 00	0.59962E 00	0.10000E 01	0.13665E 08
0.45435E 00	0.40390E 00	0.61431E 00	0.10000E 01	0.13665E 08
0.48768E 00	0.45749E 00	0.62936E 00	0.10000E 01	0.13665E 08
0.52442E 00	0.51515E 00	0.64478E 00	0.10000E 01	0.13665E 08
0.56508E 00	0.57744E 00	0.66058E 00	0.10000E 01	0.13665E 08
0.61027E 00	0.64502E 00	0.67676E 00	0.10000E 01	0.13665E 08
0.66074E 00	0.71869E 00	0.69334E 00	0.10000E 01	0.13665E 08
0.71740E 00	0.79940E 00	0.71033E 00	0.10000E 01	0.13665E 08
0.78137E 00	0.88835E 00	0.72773E 00	0.10000E 01	0.13665E 08
0.85405E 00	0.98700E 00	0.74556E 00	0.10000E 01	0.13665E 08
0.93718E 00	0.10971E 01	0.76383E 00	0.10000E 01	0.13665E 08

Substitution of Eq. (4.3) into (3.15) gives, for $U_0' = 1.0$:

$$\frac{v'(s)}{s}[s^2(m'-Y_{\dot{v}}')-sY_v']+\Psi'(s)[-s^2Y_{\dot{r}}'+s(m'-Y_r')] = \frac{10Y_\delta'(K_ts+K)\Psi'}{s+10}$$

$$\frac{v'(s)}{s}[-s^2N_{\dot{v}}'-sN_v']+\Psi'(s)[s^2(I_z'-N_{\dot{r}}')-sN_r'] = \frac{10N_\delta'(K_ts+K)\Psi'}{s+10}$$

$$\frac{u'(s)}{s}[s^2(m'-X_{\dot{u}}')-sX_u']+X_u' = \frac{10X_\delta'(K_ts+K)\Psi'}{s+10} \qquad (4.4)$$

And after manipulations Eqs. (4.4) becomes

$$\frac{v'(s)}{s}[s^3(m'-Y_{\dot{v}}')+\{10(m'-Y_{\dot{v}}')-Y_v'\}s^2+(-10Y_v')s]+\Psi'(s)[-Y_{\dot{r}}'s^3+\{(m'-Y_r')$$
$$-10Y_{\dot{r}}'\}s^2+\{10(m'-Y_r')-10Y_\delta'K_t\}s-10Y_\delta'K] = 0$$

$$\frac{v'(s)}{s}[-N_{\dot{v}}'s^3-(N_v'+10N_{\dot{v}}')s^2-10N_v's]+\Psi'(s)[s^3(I_z'-N_{\dot{r}}')+\{10(I_z'-N_{\dot{r}}')-N_r'\}s^2$$
$$-(10N_r'+10N_\delta'K_t)s-10N_\delta'K] = 0$$

$$\frac{u'(s)}{s}[s^3(m'-X_{\dot{u}}')+\{10(m'-X_{\dot{u}}')-X_u'\}s^2-10X_u's]+\Psi'(s)[-10X_\delta'K_ts-10X_\delta'K]$$
$$= -10X_u'$$
$$(4.5)$$

or

$$\frac{v'(s)}{s}[\alpha_{aA}s^3+\beta_{aA}s^2+\gamma_{aA}s+\delta_{aA}]+\Psi'(s)[\alpha_{aA}s^3+\beta_{bA}s^2+\gamma_{bA}s+\delta_{bA}] = 0$$

$$\frac{v'(s)}{s}[\alpha_{aB}s^3+\beta_{aB}s^2+\gamma_{aB}s+\delta_{aB}]+\Psi'(s)[\alpha_{bB}s^3+\beta_{bB}s^2+\gamma_{bB}s+\delta_{bB}] = 0$$

$$\frac{u'(s)}{s}[\alpha_{cC}s^3+\beta_{cC}s^2+\gamma_{cC}s+\delta_{cC}]+\Psi'(s)[\alpha_{bC}s^3+\beta_{bC}s^2+\gamma_{bC}s+\delta_{bC}] = -10Xu'$$
$$(4.6)$$

where

$$\alpha_{aA} = (m' - Y'_{\dot{v}})$$

$$\beta_{aA} = 10(m' - Y'_{\dot{v}}) - Y'_{v}$$

$$\gamma_{aA} = -10Y'_{v}$$

$$\delta_{bA} = 0$$

$$\alpha_{bA} = -Y'_{\dot{r}}$$

$$\beta_{bA} = (m' - Y'_{r}) - 10Y'_{\dot{r}}$$

$$\gamma_{bA} = 10(m' - Y'_{r}) - 10Y'_{\delta}K_{t}$$

$$\delta_{bA} = -10Y'_{\delta}K$$

$$\alpha_{aB} = -N'_{\dot{v}}$$

$$\beta_{aB} = -N'_{v} - 10N'_{\dot{v}}$$

$$\gamma_{aB} = -10N'_{v}$$

$$\delta_{aB} = 0$$

$$\alpha_{bB} = (I'_{z} - N'_{\dot{r}})$$

$$\beta_{bB} = 10(I'_{z} - N'_{\dot{r}}) - N'_{r}$$

$$\gamma_{bB} = -10N'_{r} - 10N'_{\delta} \cdot K_{t}$$

$$\delta_{bB} = -10N'_{\delta}K$$

$$\alpha_{bC} = 0$$

$$\beta_{bC} = 0$$

$$\gamma_{bC} = -10X'_{\delta}K_{t}$$

$$\delta_{bC} = -10X'_{\delta}K$$

$$\alpha_{cC} = (m' - X'_{\dot{u}})$$

$$\beta_{cC} = 10(m' - X'_{\dot{u}}) - X'_{u}$$

$$\gamma_{cC} = -10X'_{u}$$

$$\delta_{cC} = 0$$

and setting

$$\frac{v'(s)}{s} = A(s) \quad \text{or} \quad v'(t) = \dot{A}$$

$$\Psi'(s) = B(s) \quad \text{or} \quad \Psi'(t) = B$$

$$\frac{u'(s)}{s} = C(s) \quad \text{or} \quad u'(t) = \dot{C}$$

gives

$$\begin{aligned}
&\alpha_{aA}\dddot{A}+\beta_{aA}\ddot{A}+\gamma_{aA}\dot{A}+\delta_{aA}A+\alpha_{bA}\dddot{B}+\beta_{bA}\ddot{B}+\gamma_{bA}\dot{B}+\delta_{bA}B = 0\\
&\alpha_{aB}\dddot{A}+\beta_{aB}\ddot{A}+\gamma_{aB}\dot{A}+\delta_{aB}A+\alpha_{bB}\dddot{B}+\beta_{bB}\ddot{B}+\gamma_{bB}\dot{B}+\delta_{bB}B = 0 \qquad (4.8)\\
&\alpha_{cC}\dddot{C}+\beta_{cC}\ddot{C}+\gamma_{cC}\dot{C}+\delta_{cC}C+\alpha_{bC}\dddot{B}+\beta_{bC}\ddot{B}+\gamma_{bC}\dot{B}+\delta_{bC}B = IF3
\end{aligned}$$

or

$$\begin{aligned}
\alpha_{aA}\dddot{A}+\alpha_{bA}\dddot{B} &= I1\\
\alpha_{aB}\dddot{A}+\alpha_{bB}\dddot{B} &= I2 \qquad (4.9)\\
\alpha_{cC}\dddot{C}+\alpha_{bC}\dddot{B} &= I3
\end{aligned}$$

where

$$\begin{aligned}
IF3 &= -10X_u'\\
I1 &= -\beta_{aA}\ddot{A}-\gamma_{aA}\dot{A}-\delta_{aA}A-\beta_{bA}\ddot{B}-\gamma_{bA}\dot{B}-\delta_{bA}B\\
I2 &= -\beta_{aB}\ddot{A}-\gamma_{aB}\dot{A}-\delta_{aB}A-\beta_{bB}\ddot{B}-\gamma_{bB}\dot{B}-\delta_{bB}B \qquad (4.10)\\
I3 &= -\beta_{cC}\ddot{C}-\gamma_{cC}\dot{C}-\delta_{cC}C-\beta_{bC}\ddot{B}-\gamma_{bC}\dot{B}-\delta_{bC}B
\end{aligned}$$

Now the computer program I can be modified accordingly to include the control action, and the resulting computer program II was implemented and simulated for the Class D surface ship, and for an arbitrary pair of values of K = 0.78137 and K_t = 0.88835 from Table III, corresponding to a

critically damped (ζ=1.0) response, for the following course keeping case:

> The ship is originally on a straightforward motion ($U_0' = 1.0$) at a specified course. Due to external disturbances (waves, wind) it acquires a certain yaw, $\Psi = 0.2$ and a certain yaw rate, $\dot{\Psi} = 0.1$. The results of the control action to bring and keep the ship back to the original course are shown in Fig. 12.

The existing steady state error can be considered negligible and furthermore justified since the simulation, as it was carried out, included the effect of the coupling among the three equations of motion, whereas this affect was neglected in the procedure for optimization of K and K_t.

B. THE DISTANCE KEEPING LOOP

1. A Special Case

The feedback control loop in a block diagram form is shown in Fig. 13. Here a somewhat unrealistic but helpful assumption is made, that the control's objective is to keep the lateral motion (sway) of one individual ship to zero, with respect to its original path, or to the set of axes placed in space. This assumption will be relaxed later in the general case of two ships involved in the replenishment at sea operation, where an initial lateral separation between the ships is established.

Therefore the loop is now a zero input reference one, and the main important output variables are the sway, y, and the sway rate, $\dot{y}$.



Figure 12. The Course Keeping System's Response



Figure 13. The Distance Keeping Loop.

The equations derived from Fig. 5, and the transfer functions on page 32 are repeated here for further explanation of Fig. 13.

$$\dot{y}' = u'\sin\Psi' + v'\cos\Psi'$$

$$\dot{x} = u'\cos\Psi' - v'\sin\Psi'$$

$$\frac{v'(s)}{\delta(s)} = \frac{K_v(s+Z_v)}{s^2+\beta s+\gamma} \tag{3.27}$$

$$\frac{\Psi'(s)}{\delta(s)} = \frac{K_r(s+Z_r)}{s(s^2+\beta s+\gamma)} \tag{3.28}$$

$$\frac{u'(s)}{\delta(s)} = \frac{K_u}{s+P_u} \tag{3.29}$$

2. Computer Program for the Controlled Plant

The relation between δ and δd is again $\delta = \frac{10}{s+10}\delta d$ (4.11) and $\delta d = (K_t\, s + K)y'$.

Substitution of Eq. (4.11) into (3.15) for $U_0' = 1.0$ gives

$$\frac{v'(s)}{s}\left[\alpha_{aA}s^3+(\beta_{aA}+10\alpha_{aA})s^2+10\beta_{aA}s+10\gamma_{aA}\right]$$
$$+\Psi'(s)\left[\alpha_{bA}s^3+(\beta_{bA}+10\alpha_{bA})s^2+10\beta_{bA}s+10\gamma_{bA}\right] = IF1$$

$$\frac{v'(s)}{s}\left[\alpha_{aB}s^3+(\beta_{aB}+10\alpha_{aB})s^2+10\beta_{aB}s+10\gamma_{aB}\right]$$
$$+\Psi'(s)\left[\alpha_{bB}s^3+(\beta_{bB}+10\alpha_{bB})s^2+10\beta_{bB}s+10\gamma_{bB}\right] = IF2$$

$$\frac{u'(s)}{s}\left[\alpha_{cC}s^3+(\beta_{cC}+10\alpha_{cC})s^2+10\beta_{cC}s+10\gamma_{cC}\right] = IF3$$

(4.12)

where

$$IF1 = 10Y'_{\delta}\cdot\delta d = 10KA1\cdot\delta d$$

$$IF2 = 10N'_{\delta}\cdot\delta d = 10KB1\cdot\delta d$$

$$IF3 = 10X'_{\delta}\cdot\delta d - 10X_u' = 10KC1\cdot\delta d - 10X_u'$$

and setting

$$\frac{v'(s)}{s} = A(s) \quad \text{or} \quad v'(t) = \dot{A}$$

$$\Psi'(s) = B(s) \quad \text{or} \quad \Psi'(t) = B$$

$$\frac{u'(s)}{s} = C(s) \quad \text{or} \quad u'(s) = \dot{C}$$

gives

$$\begin{aligned}
&\alpha'_{aA}\dddot{A}+\beta'_{aA}\ddot{A}+\gamma'_{aA}\cdot\dot{A}+\alpha'_{bA}\cdot\dddot{B}+\beta'_{bA}\cdot\ddot{B}+\gamma'_{bA}\cdot\dot{B} = IF1\\
&\alpha'_{aB}\dddot{A}+\beta'_{aB}\ddot{A}+\gamma'_{aB}\dot{A}+\alpha'_{bB}\ddot{B}+\beta'_{bB}\ddot{B}+\gamma'_{bB}\dot{B} = IF2 \qquad (4.13)\\
&\alpha'_{cC}\dddot{C}+\beta'_{cC}\ddot{C}+\gamma'_{cC}\dot{C} = IF3
\end{aligned}$$

or

$$\begin{aligned}
&\alpha'_{aA}\dddot{A}+\alpha'_{bA}\dddot{B} = I1\\
&\alpha'_{aB}\dddot{A}+\alpha'_{bB}\dddot{B} = I2\\
&\alpha'_{cC}\dddot{C} = I3
\end{aligned}$$

where

$$\begin{aligned}
I1 &= IF1-\beta'_{aA}\ddot{A}-\gamma'_{aA}\dot{A}-\beta'_{bA}\ddot{B}-\gamma'_{bA}\dot{B}\\
I2 &= IF2-\beta'_{aB}\ddot{A}-\gamma'_{aB}\dot{A}-\beta'_{bB}\ddot{B}-\gamma'_{bB}\dot{B} \qquad (4.14)\\
I3 &= IF3
\end{aligned}$$

and

$$\begin{aligned}
\alpha'_{aA} &= \alpha_{aA} & \gamma'_{aB} &= 10\beta_{aB}\\
\beta'_{aA} &= \beta_{aA}+10\alpha_{aA} & \alpha'_{bB} &= \alpha_{bB}\\
\gamma'_{aA} &= 10\beta_{aA} & \beta'_{bB} &= \beta_{bB}+10\alpha_{bB}\\
\alpha'_{bA} &= \alpha_{bA} & \gamma'_{bB} &= 10\beta_{bB} \qquad (4.14a)\\
\beta'_{bA} &= \beta_{bA}+10\alpha_{bA} & \alpha'_{cC} &= \alpha_{cC}\\
\gamma'_{bA} &= 10\beta_{bA} & \beta'_{cC} &= \beta_{cC}+10\alpha_{cC}\\
\alpha'_{aB} &= \alpha_{aB} & \gamma'_{cC} &= 10\beta_{cC}\\
\beta'_{aB} &= 10\alpha_{aB}+\beta_{aB}
\end{aligned}$$

Now the computer program I is modified to reflect the appropriate control action, and this results to computer program III.

3. Determination of K and K_t for a Desired Performance

The proper values for K and K_t are again to be determined for the system's response under the condition: $\zeta = 1.0$.

For small angles of yaw it is true that $\sin \Psi' \simeq \Psi'$ and $\cos \Psi' \simeq 1.0$, and therefore the Eq. $y' = u' \sin\Psi' + v' \cos \Psi'$ can be written as $y' \simeq \Psi' + v'$. (4.15)

From Eqs. (3.27 and 3.28) respectively:

$$\Psi' = \frac{K_r(s+Z_r)}{s(s^2+\beta s+\gamma)} \delta(s)$$

$$v' = \frac{K_v(s+Z_v)}{s^2+\beta s+\gamma} \delta(s)$$

and making use of Eq. (4.11) gives

$$\Psi' = \frac{10K_r(s+Z_r)\cdot\delta d}{s(s+10)(s^2+\beta s+\gamma)}$$

$$v' = \frac{10K_v(s+Z_v)\delta d}{(s+10)(s^2+\beta s+\gamma)}$$

Therefore Eq. (4.15) becomes:

$$\dot{y}'/\delta d = \frac{10K_r(s+Z_r)+10sK_v(s+Z_v)}{s(s+10)(s^2+\beta s+\gamma)}$$

and

$$y'/\delta d = \frac{10K_r(s+Z_r)+10sK_v(s+Z_v)}{s^2(s+10)(s^2+\beta s+\gamma)} \quad (4.16)$$

But from Fig. 13:

$$\delta d = (K_t s+K)y' \quad (4.17)$$

Now based on Eqs. (4.16 and 4.17) the equivalent of the control loop of Fig. 13 is given in Fig. 14 in agreement with the general form of Fig. 11. Therefore the closed loop transfer function is now:

$$\frac{G}{1-GH} = \frac{10K_r(s+Z_r)+10s\,K_v(s+Z_v)}{s^2(s+10)(s^2+\beta s+\gamma)-(K_t s+K)[10K_r(s+Z_r)+10sK_v(s+Z_v)]} \tag{4.18}$$

and the characteristic equations is

$$s^5+(10+\beta)s^4+(10\beta+\gamma)s^3+10\gamma s^2-10K_rK_ts^2-10K_r(K+K_tZ_r)s-10K_rKZ_r$$
$$-10K_vK_ts^3-10K_vZ_v\,K_ts^2-10K_vKS^2-10K_vZ_vKS = 0$$

or

$$s^5+(10+\beta)s^4+[(10\beta+\gamma)-10K_vK_t]s^3$$
$$+[-10K_vK-(10K_r+10K_vZ_v)K_t+10\gamma]s^2$$
$$-[(-10K_vZ_v-10K_r)K-10K_rZ_rK_t]s+(-10K_rZ_r)K = 0 \tag{4.19}$$

Considering again the Class D surface ship and evaluating Eqs. (3.30), according to the values of Table II gives:

$$Kr = -1.74425$$
$$Zr = 1.24744$$
$$Kv = 0.32126$$
$$Zv = 2.288$$
$$\beta = 3.227$$
$$\gamma = 2.0$$

And now Eq. (4.19) becomes:

$$s^5+32.27s^4+[-3.2126K_t+34\cdot27]s^3+[-3.2126K+10.0921K_t+20.0]s^2$$
$$+[10.0921K+21.7584K_t]s+21.784K = 0 \qquad (4.20)$$

The PARAM "A" computer program was simulated for the case of Eq. (4.20) and for $U_0' = 1.0$ and a sample of the computer result containing permissible pairs of values of K and K_t is given in Table IV.



Figure 14. The Equivalent Distance Control Loop

4. Computer Simulation

Two different problems were encountered:

a. The station keeping case

The ship, due to external disturbances, has acquired a certain sway, y = 0.1 and a certain sway rate,

TABLE IV

APPROPRIATE VALUES OF PARAMETERS K AND K_t

K	K_t	Ω	ζ	Third Parameter
0.89184E 06	0.58816E 04	0.12927E 03	0.80000E 00	0.13665E 08
0.96373E 06	0.62283E 04	0.13244E 03	0.80000E 00	0.13665E 08
0.10413E 07	0.65935E 04	0.13568E 03	0.80000E 00	0.13665E 08
0.11249E 07	0.69782E 04	0.13901E 03	0.80000E 00	0.13665E 08
0.72336E-02	0.15389E 00	0.10000E 00	0.10000E 01	0.13665E 08
0.75513E-02	0.15703E 00	0.10245E 00	0.10000E 01	0.13665E 08
0.78822E-02	0.16022E 00	0.10496E 00	0.10000E 01	0.13665E 08
0.82269E-02	0.16346E 00	0.10753E 00	0.10000E 01	0.13665E 08
0.85857E-02	0.16676E 00	0.11017E 00	0.10000E 01	0.13665E 08
0.89593E-02	0.17011E 00	0.11286E 00	0.10000E 01	0.13665E 08
0.93483E-02	0.17351E 00	0.11563E 00	0.10000E 01	0.13665E 08
0.97533E-02	0.17697E 00	0.11846E 00	0.10000E 01	0.13665E 08
0.10175E-01	0.18049E 00	0.12137E 00	0.10000E 01	0.13665E 08
0.10614E-01	0.18406E 00	0.12434E 00	0.10000E 01	0.13665E 08
0.11070E-01	0.18769E 00	0.12738E 00	0.10000E 01	0.13665E 08
0.11546E-01	0.19138E 00	0.13051E 00	0.10000E 01	0.13665E 08
0.12041E-01	0.19512E 00	0.13370E 00	0.10000E 01	0.13665E 08
0.12556E-01	0.19893E 00	0.13698E 00	0.10000E 01	0.13665E 08
0.13092E-01	0.20280E 00	0.14033E 00	0.10000E 01	0.13665E 08
0.13650E-01	0.20673E 00	0.14377E 00	0.10000E 01	0.13665E 08
0.14232E-01	0.21072E 00	0.14730E 00	0.10000E 01	0.13665E 08
0.14837E-01	0.21478E 00	0.15090E 00	0.10000E 01	0.13665E 08
0.15467E-01	0.21890E 00	0.15460E 00	0.10000E 01	0.13665E 08
0.16123E-01	0.22310E 00	0.15839E 00	0.10000E 01	0.13665E 08
0.16807E-01	0.22736E 00	0.16227E 00	0.10000E 01	0.13665E 08
0.17519E-01	0.23170E 00	0.16624E 00	0.10000E 01	0.13665E 08
0.18262E-01	0.23611E 00	0.17032E 00	0.10000E 01	0.13665E 08
0.19036E-01	0.24060E 00	0.17449E 00	0.10000E 01	0.13665E 08
0.19844E-01	0.24518E 00	0.17877E 00	0.10000E 01	0.13665E 08
0.20686E-01	0.24983E 00	0.18315E 00	0.10000E 01	0.13665E 08
0.21566E-01	0.25458E 00	0.18763E 00	0.10000E 01	0.13665E 08
0.22485E-01	0.25942E 00	0.19223E 00	0.10000E 01	0.13665E 08
0.23446E-01	0.26436E 00	0.19694E 00	0.10000E 01	0.13665E 08
0.24451E-01	0.26940E 00	0.20176E 00	0.10000E 01	0.13665E 08
0.25503E-01	0.27455E 00	0.20671E 00	0.10000E 01	0.13665E 08
0.26606E-01	0.27982E 00	0.21177E 00	0.10000E 01	0.13665E 08
0.27762E-01	0.28521E 00	0.21696E 00	0.10000E 01	0.13665E 08
0.28976E-01	0.29074E 00	0.22227E 00	0.10000E 01	0.13665E 08
0.30252E-01	0.29641E 00	0.22772E 00	0.10000E 01	0.13665E 08
0.31594E-01	0.30223E 00	0.23330E 00	0.10000E 01	0.13665E 08

$\dot{y}$ = 0.01 (it has been moved from its original position laterally by: y' x L feet, and the disturbance is continuing).

The computer program III was simulated for the Class D ship, for U_0' = 1.0, and for an arbitrary pair of K = 0.0225 and K_t = 0.25942 of Table III, corresponding to a critically damped (ζ=1.0) response. The result is shown in Fig. 15.

b. The Station Changing Case

The ship is originally on a straightforward motion at a specified course. It is desired to move to a course parallel to the original one, but at a distance D = D' x L from its original position laterally, as shown in Fig. 16.

The control loop of Fig. 13 is now modified as shown in Fig. 17 by the addition of the input reference $-D'$. The input reference is given a negative sign because for a desired lateral translation of the ship to its starboard direction, a negative rudder δ is required. It is now clear that the ordered rudder angle becomes $\delta d = K(y'-D')+K_t \cdot \dot{y}'$, and therefore the computer program III is modified accordingly to yield computer program IV.

For this station changing case, computer program IV was simulated, for U_0'=1.0 of the Class D ship and for the same pair of K = 0.0225 and K_t = 0.25942 of Table III and the result is shown in Fig. 18.



Figure 15. The Station Keeping System's Response



Figure 16. Station Changing



Figure 17. The Distance Changing Control Loop.



Figure 18. The Station-Changing System's Response

V. AN ACTUAL REPLENISHMENT AT SEA PROBLEM

A. INCLUSION OF INTERACTION FORCES AND MOMENTS

1. Characteristic Values

During Newton's experiment [3], for each position of one ship relative to the other, two forces were measured on each F_1 and F_2 as in Fig. 19. These two forces can be represented by a single force $F_I = F_1 + F_2$ and a moment M_I, the magnitude of which depends upon the position about which moments are taken. If any of those forces are to be included in the equations of motion, they have to be represented by a force and a moment about the origin, and therefore the center of gravity.

All forces and moments in Figs. 1 and 3 are with respect to a point, called the "neutral point N" at which neglecting transient effects, any lateral force applied will cause no change



Figure 19. The Interactive Forces and Moments

in heading, although it will cause a change in course. It has experimentally been found that the neutral point lies at 1/5 the length of the ship from the bow.

From Fig. 3 (100 ft. lateral separation) the non-dimensional force and moment of one of the two ships at the exactly abeam position are respectively

$$F_{I_{(N)}} = 2.16 \cdot 10^{-4} \text{ and } M_{I_{(N)}} = -0.8 \cdot 10^{-4} .$$

If the center of gravity is assumed to be at the geometric center of symmetry of the ship, then the forces F_1 and F_2 equivalent to $F_{I_{(N)}}$ and $M_{I_{(N)}}$ can be represented by a single force $F_{I_{(G)}}$ and a moment $M_{I_{(G)}}$ about the center of gravity that can be found to be:

$$F_{I_{(G)}} = 2.16 \cdot 10^{-4} \text{ and } M_{I_{(G)}} = -0.152 \cdot 10^{-4}$$

as shown in Fig. 20.



Figure 20. Equivalent Forces and Moments.

2. Modification of the Equations of Motion

If YI and NI are the nondimensionalized force and moment acting on a ship when exactly alongside another, then the equations for this ship become (for $U_0' = 1.0$):

$$\frac{v'(s)}{s}[\alpha_{aA}s^2+\beta_{aA}s+\gamma_{aA}]+\Psi'(s)[\alpha_{bA}s^2+\beta_{bA}s+\gamma_{bA}] = Y_\delta'\cdot\delta(s)+YI(s)$$

$$\frac{v'(s)}{s}[\alpha_{aB}s^2+\beta_{aB}s+\gamma_{aB}]+\Psi'(s)[\alpha_{bB}s^2+\beta_{bB}s+\gamma_{bB}] = N_\delta'\cdot\delta(s)+NI(s)$$

$$\frac{u'(s)}{s}[\alpha_{cC}s^2+\beta_{cC}s+\gamma_{cC}] = X_\delta'\cdot\delta(s) - Xu'$$

Since $\delta(s) = 10\delta d(s)/s+10$, then Eqs. (5.1) can be written:

$$\frac{v'(s)}{s}[\alpha_{aA}s^3+(\beta_{aA}+10\alpha_{aA})s^2+10\beta_{aA}s+10\gamma_{aA}]$$
$$+\Psi'(s)[\alpha_{bA}s^3+(\beta_{bA}+10\alpha_{bA})s^2+10\beta_{bA}s+10\gamma_{bA}] = 10Y_\delta'\cdot\delta d(s)+YI(s)$$

$$\frac{v'(s)}{s}[\alpha_{aB}s^3+(\beta_{aB}+10\alpha_{aB})s^2+10\beta_{aB}s+10\gamma_{aB}]$$
$$+\Psi'(s)[\alpha_{bB}s^3+(\beta_{bB}+10\alpha_{bB})s^2+10\beta_{bB}s+10\gamma_{bB}] = 10N_\delta'\cdot\delta d(s)+NI(s)$$

$$\frac{u'(s)}{s}[\alpha_{cC}s^3+(\beta_{cC}+10\alpha_{cC})s^2+10\beta_{cC}s+10\gamma_{cC}] = 10X_\delta'\cdot\delta d(s) - 10X_u' \qquad (5.2)$$

The following important assumptions will become the basis of all further investigation of the replenishment at sea problem:

a. The two ships are identical.

b. All hydrodynamic coefficients are not affected by the intermingling of the water pressures between the ships, and the motions of the ships, and therefore they remain constant.

c. The two ships are considered already as being alongside each other.

d. The forces and moments acting on the ships are identical (in absolute value), and they are as shown in Fig. 20.

e. The changes of YI and NI, due to relative motions of the ships, are considered negligible and $\dot{Y}I = \dot{N}I = 0$.

f. The subscript 1 attached to the quantities of the equations of motion characterizes the replenishing ship, and correspondingly, subscript 2 indicates quantities referring to the receiving ship.

g. A pair of values of the parameters K and K_t of either Table III or IV will be given the definition "optimal," in the sense that it constitutes a proper pair of parameter values, for which the performance of the system corresponds to a ζ=1.0 condition.

Therefore under the above assumptions the equations for replenishing ship should be:

$$\frac{v_1'(s)}{s}[\alpha'_{aA}s^3+\beta'_{aA}s^2+\gamma'_{aA}s+\delta'_{aA}]+\Psi_1'(s)[\alpha'_{bA}s^3+\beta'_{bA}s^2+\gamma'_{bA}s+\delta'_{bA}] = 10Y'_{\delta}\cdot\delta d_1(s)+YI1$$

$$\frac{v_1'(s)}{s}[\alpha'_{aB}s^3+\beta'_{aB}s^2+\gamma'_{aB}s+\delta'_{aB}]+\Psi_1'(s)[\alpha'_{bB}s^3+\beta'_{bB}s^2+\gamma'_{bB}s+\delta'_{bB}] = 10N'_{\delta}\cdot\delta d_1(s)+NI1 \quad (5.3)$$

$$\frac{u_1'(s)}{s}[\alpha'_{cC}s^3+\beta'_{cC}s^2+\gamma'_{cC}s+\delta'_{cC}] = 10X'_{\delta}\cdot\delta d_1(s) - 10Xu'$$

Or setting

$$\frac{v_1'(s)}{s} = A_1(s) \quad \text{or} \quad v_1'(t) = \dot{A}_1$$

$$\Psi_1'(s) = B_1(s) \quad \text{or} \quad \Psi_1'(t) = B_1$$

$$\frac{u_1'(s)}{s} = C_1(s) \quad \text{or} \quad u_1'(t) = \dot{C}_1$$

gives

$$\begin{aligned}
&\alpha'_{aA}\dddot{A}_1+\beta'_{aA}\ddot{A}_1+\gamma'_{aA}\dot{A}_1+\alpha'_{bA}\dddot{B}_1+\beta'_{bA}\ddot{B}_1+\gamma'_{bA}\dot{B}_1 = IF1_1\\
&\alpha'_{aB}\dddot{A}_1+\beta'_{aB}\ddot{A}_1+\gamma'_{aB}\dot{A}_1+\alpha'_{bB}\dddot{B}_1+\beta'_{bB}\ddot{B}_1+\gamma'_{bB}\dot{B}_1 = IF2_1 \qquad (5.4)\\
&\alpha'_{cC}\dddot{C}_1+\beta'_{cC}\ddot{C}_1+\gamma'_{cC}\dot{C}_1 = IF3_1
\end{aligned}$$

where

$$\begin{aligned}
IF1_1 &= 10Y'_\delta \cdot \delta d_1 + YI1\\
IF2_1 &= 10N'_\delta \cdot \delta d_1 + NI1\\
IF3_1 &= 10X'_\delta \cdot \delta d1 - 10X'u
\end{aligned}$$

and for the primed coefficients the relations (4.14a) are valid. Furthermore Eqs. (5.4) can be written:

$$\begin{aligned}
&\alpha'_{aA}\dddot{A} +\alpha'_{bA}\dddot{B}_1 = I1_1\\
&\alpha'_{aB}\dddot{A}_1+\alpha'_{bB}\dddot{B}_1 = I2_1 \qquad (5.5)\\
&\alpha'_{cC}\dddot{C}_1 = I3_1
\end{aligned}$$

where

$$I1_1 = IF1_1 - \beta'_{aA}\cdot\ddot{A}_1 - \gamma'_{aA}\dot{A}_1 - \beta'_{bA}\ddot{B}_1 - \gamma'_{bA}\dot{B}_1$$

$$I2_1 = IF2_1 - \beta'_{aB}\cdot\ddot{A}_1 - \gamma'_{aB}\dot{A}_1 - \beta'_{bB}\ddot{B}_1 - \gamma'_{bB}\dot{B}_1$$

$$I3_1 = IF3_1 - \beta'_{cC}\ddot{C}_1 - \gamma'_{cC}\dot{C}_1$$

In the same fashion equations for the receiving ship can be found to be, for $U'_{0_2} = 10$:

$$\begin{aligned}
\alpha'_{aA}\dddot{A}_2 + \beta'_{aA}\ddot{A}_2 + \gamma'_{aA}\dot{A}_2 + \alpha'_{bA}\dddot{B}_2 + \beta'_{bA}\cdot\ddot{B}_2 + \gamma'_{bB}\dot{B}_2 &= IF1_2 \\
\alpha'_{aB}\dddot{A}_2 + \beta'_{aB}\ddot{A}_2 + \gamma'_{aA}\dot{A}_2 + \alpha'_{bB}\dddot{B}_2 + \beta'_{bB}\cdot\ddot{B}_2 + \gamma'_{bB}\dot{B}_2 &= IF2_2 \qquad (5.6) \\
\alpha'_{cC}\dddot{C}_2 + \beta'_{cC}C_2 + \gamma'_{cC}C_2 &= IF3_2
\end{aligned}$$

where

$$\begin{aligned}
IF1_2 &= 10Y'_{\delta}\cdot\delta d + YI2 \\
IF2_2 &= 10N'_{\delta}\cdot\delta d + NI2 \\
IF3_2 &= 10X'_{\delta}\cdot\delta d - 10Xu'
\end{aligned}$$

or

$$\begin{aligned}
\alpha'_{aA}\dddot{A}_2 + \alpha'_{bA}\dddot{B}_2 &= I1_2 \\
\alpha'_{aB}\dddot{A}_2 + \alpha'_{bB}\dddot{B}_2 &= I2_2 \qquad (5.7) \\
a'_{cC}\dddot{C}_2 &= I3_2
\end{aligned}$$

where

$$I1_2 = IF1_2 - \beta'_{aA}\ddot{A}_2 - \gamma_{aA}\dot{A}_2 - \beta'_{bA}\ddot{B}_2 - \gamma'_{bA}\cdot\dot{B}_2$$

$$I2_2 = IF2_2 - \beta'_{aB}\ddot{A}_2 - \gamma'_{aB}\dot{A}_2 - \beta'_{bB}\ddot{B}_2 - \gamma'_{bB}\cdot\dot{B}_2$$

$$I3_2 = IF3_2 - \beta'_{cC}\ddot{C}_2 - \gamma'_{cC}\dot{C}_2$$

3. The Behavior of the Ships Under the Influence of Interactive Forces and Moments Without Controls.

Equations (5.7) give computer program V. This computer program in which δd_2=DD2 = 0, was simulated for the class D ship, for U'_{0_2} = 1.0 and the results showing the sway and yaw of the receiving ship are shown in Figs. 21 and 22, respectively. If the replenishing ship were simulated instead, with δd_1 = DD1 = 0, the results would have been identical but with a sign reversed.

B. THE PROPOSED METHODS OF CONTROL

1. Method I

In this method of controlling the maneuvering of the two ships involved in the replenishment at sea operation, the control of the replenishing ship should be made sensitive to the measured quantities of its yaw and yaw rate, and the control of the receiving ship should be made sensitive to the measured quantities of its yaw, yaw rate, relative sway and relative sway rate. If this is the case, the feedback control loop for the replenishing ship should be a course keeping one as shown in Fig. 9. The relative sway and relative sway rate could be made available by means of one or two sensing devices



Figure 21. Sway 2 Vs. Time



Figure 22. Yaw 2 Vs. Time

(radars) aboard the receiving ship that would provide a continuing signaling of the actual distance and its rate of change between the ships as shown in Fig. 23.

The feedback control loop for the receiving ship should be the one shown in Fig. 24. From Figs. 9 and 24 it is evident that

$$\delta d_1 = DDC1 = (K_1+K_{t_1}s)\Psi_1' = K1\cdot B_1 + KT1\cdot BD1$$

$$\delta d_2 = DDC2 + DDD2 = (K_2+K_{t_2}s)\Psi_2' + (K_2'+K_{t_2}s)(y_2'-y_1')$$

$$= K2\cdot B2 + KT2\cdot BD2 + KP2\cdot D + KTP2\cdot DDOT$$

The computer program VI was simulated for two class D ships with $U_{0_1}' = U_{0_2}' = 1.0$ and the results are shown in Figs. 25 through 31. It is noted here that K_1 and K_{t_1} are given the values corresponding to an optimal pair, whereas the pairs K_2-K_{t_2} and K_2-K_{t_2} do not necessarily have to be optimal.

2. Method II

This method is exactly the same with the Method I except that now the values of K_1 and K_{t_1} for the replenishing ship are made slightly different than the optimal values used in Method I. In this case the replenishing ship is brought by the control action to such an equilibrium angle of yaw (Ψ_1'), that causes its heading to become not parallel to its original one. Then it is shown that the receiving ship is forced to keep proper separation between ships, keeping parallel to the new heading of the replenishing ship.



D_0 - Original desired separation

D_a - Actual distance measured by sensor

Relative sway $D = y_2' - y_1' = D_a - D_0$

Relative sway rate - $\dot{D}_a$

Figure 23. Relative Sway and Sway Rate.



Figure 24. The Complete Course and Station Keeping Loop

The computer program VII was simulated for two class D ships, with $U'_{0_1} = U'_{0_2} = 1.0$ and the results are shown in Fig. 32 through Fig. 36.

3. Method III

In this method the controls of both the replenishing ship and the receiving ship are made sensitive to their respective yaw, yaw rate, relative sway and relative sway rate. In this case Fig. 24 applies for both ships and the feedback controls should be:

$$\delta_{d_1} = \text{DDC1} + \text{DDD1} = (K_1+K_{t_1}s)\Psi'_1+(K'_1+K_{t_1}s)(y'_1-y'_2)$$

$$= \text{K1}\cdot\text{B1} + \text{KT1}\cdot\text{BD1} - \text{KP1}\cdot\text{D} - \text{KTP1}\cdot\text{DDOT}$$

$$\delta_{d_2} = \text{K2}\cdot\text{B2} + \text{KT2}\cdot\text{BD2} + \text{KP2}\cdot\text{D} + \text{KTP2}\cdot\text{DDOT}$$

The computer program VIII was simulated for two class D ships, with $U'_{0_1} = U'_{0_2} = 1.0$ and the results are shown in Fig. 37 through Fig. 41.



Figure 25. Yaw l Vs. Time.



Figure 26. Sway 1 Vs. Time



Figure 27. Surge 1 Vs. Time



Figure 28. Yaw 2 Vs. Time



Figure 29. Sway 2 Vs. Time



Figure 30. Surge 2 Vs. Time



Figure 31. Trajectories of the Two Ships



Figure 32. Yaw 1 Vs. Time



Figure 33. Sway 1 Vs. Time



Figure 34. Yaw 2 Vs. Time



Figure 35. Sway 2 Vs. Time



Figure 36. Trajectories of the Two Ships



Figure 37. Yaw 1 Vs. Time



Figure 38. Sway 1 Vs. Time



Figure 39. Yaw 2 Vs. Time



Figure 40. Sway 2 Vs. Time



Figure 41. Trajectories of the Two Ships

VI. CONCLUSIONS

Comparison of the results of all three methods proposed leads to the conclusion that method I (complying with today's practiced Naval tactics, that the replenishing ship is only responsible for course or path keeping) is by far the best one. Of course the other two methods, in open sea, and when no other ships are present could still be considered feasible ones.

From Figs. 25 and 28 it is seen that if no corrective rudder (control) is applied, the interaction moments will cause the ships to yaw outwards, bringing their sterns toward each other. As the ships yaw the inwards hydrodynamic forces will come into action. If the exact and proper rudder is applied now, as in method I, this will counteract the interaction moment and bring the replenishing ship back to a position of equilibrium at a small angle of yaw to the direction of advance. In method I this angle of yaw is such that does not cause any change of course, since it produces the exact necessary lift force that balances the inward interaction force.

In method II, due to values of K1 and KT1 different than the optimal ones, and in method III, due to the inclusion of the distance control loop, the applied rudder angle for the replenishing ship does not yield the proper equilibrium angle of yaw. In these methods although the moment of the force from the rudder can counteract the interaction moment, the rudder force is insufficient to balance the interaction force,

and the replenishing ship is therefore changing course, which the receiving ship is forced to follow.

COMPUTER PROGRAM I

```
*THIS PROGRAM SIMULATES THE DYNAMICS OF A SURFACE SHIP.
*THE EQUATIONS OF MOTION ARE TO BE IN THE FORM:
*(AAAS2+BAAS+GAA)A+(ABAS2+BBAS+GBA)B+(ACAS2+BCAS+GCA)C=
*KA1*D1+KA2*D2+NA
*(AABS2+BABS+GAB)A+(ABBS2+BBBS+GBB)B+(ACBS2+BCBS+GCB)C=
*KB1*D1+KB2*D2+NB
*(AACS2+BACS+GAC)A+(ABCS2+BBCS+GBC)B+(ACCS2+BCCS+GCC)C=
*KC1*D1+KC2*D2+NC
*A,BAND C ARE THE VARIABLES.
*D1,D2 ARE THE DEFLECTIONS OF THE RUDDER(S).
*NA,NB,NC ARE TERMS IN WHICH ANY EXTERNAL FORCES OR MOMENTS,
*OR NONLINEAR TERMS CAN BE INCLUDED.
*AAB,BAB...,KA1...MUST BE DEFINED IN SECTION 2 AS FUNCTIONS
*OF THE HYDRODYNAMIC COEFFICIENTS,THE VALUES OF WHICH ARE
*INTRODUCED IN SECTION 1.
*NO ORDER IS REQUIRED.
*IN SECTION 3 THE VARIABLES ARE DEFINED,E.G. YAW=B.
*THE FIRST AND SECOND DERIVATIVES OF THE VARIABLES ARE:
*ADOT,BDOT,CDOT,ADDOT,BDDOT,CDDOT.
*IF THE REQUIRED SOLUTION INVOLVES TWO EQUATIONS,SET ACC=1.,
*THE SOLUTION WILL BE IN TERMS OF A AND B.
*UNDEFINED TERMS ARE SET AUTOMATICALLY TO ZERO,UP
*TO A MAXIMUM OF 85.
*SECTION 4 IS THE PROGRAMMED SIMULATION.
*SECTION 1 -COEFFICIENTS FOR A PARTICULAR SHIP
PARAM D1=0.1
PARAM M=0.0045
PARAM IZ=0.0003
PARAM NR=-0.0012
PARAM NRD=-0.0002
PARAM NV=-0.0012
PARAM NVD=-0.0001
PARAM KB1=-0.00084
PARAM YR=0.004
PARAM YRD=-0.0002
PARAM YV=-0.0063
PARAM YVD=-0.0025
PARAM KA1=0.0019
PARAM XU=-0.0012
PARAM XUD=-0.00036
PARAM KC1=-0.0011
*SECTION 2 -PARAMETERS CALCULATIONS
       AAA=M-YVD
       BAA=-YV
       ABA=-YRD
       BBA=M-YR
       AAB=-NVD
       BAB=-NV
       ABB=IZ-NRD
       BBB=-NR
       ACC=M-XUD
       BCC=-XU
       NC=-XU
       COFAA=ABB*ACC-ACB*ABC
       COFAB=-(ABA*ACC-ACA*ABC)
       COFAC=ABA*ACB-ABB*ACA
       COFBA=-(AAB*ACC-ACB*AAC)
       COFBB=AAA*ACC-ACA*AAC
       COFBC=-(AAA*ACB-ACA*AAB)
       COFCA=AAB*ABC-ABB*AAC
       COFCB=-(AAA*ABC-ABA*AAC)
       COFCC=AAA*ABB-ABA*AAB
       S1=AAA*ABB*ACC+AAB*ABC*ACA+AAC*ACB*ABA
       S2=ACA*ABB*AAC+ACB*ABC*AAA+ACC*AAB*ABA
```

```
      DEL=S1-S2
*SECTION 3 -PHYSICAL DEFINITIONS
      YAW=B
      SWAY=Y
      SURGE=X
*SECTION 4 -PROGRAMMED SIMULATION
      YDOT=CDOT*SIN(YAW)+ADOT*COS(YAW)
      Y=INTGRL(0.,YDOT)
      XDOT=CDOT*COS(YAW)-ADOT*SIN(YAW)
      X=INTGRL(0.,XDOT)
      ADDOT=(COFAA*I1+COFAB*I2+COFAC*I3)/DEL
      ADOT=INTGRL(0.,ADDOT)
      A=INTGRL(0.,ADOT)
      BDDOT=(COFBA*I1+COFBB*I2+COFBC*I3)/DEL
      BDOT=INTGRL(0.,BDDOT)
      B=INTGRL(0.,BDOT)
      CDDOT=(COFCA*I1+COFCB*I2+COFCC*I3)/DEL
      CDOT=INTGRL(0.,CDDOT)
      C=INTGRL(0.,CDOT)
      I1=-BAA*ADOT-GAA*A-BBA*BDOT-GBA*B-BCA*CDOT-GCA*C+IF1
      I2=-BAB*ADOT-GAB*A-BBB*BDOT-GBB*B-BCB*CDOT-GCB*C+IF2
      I3=-BAC*ADOT-GAC*A-BBC*BDOT-GBC*B-BCC*CDOT-GCC*C+IF3
      IF1=KA1*D1+KA2*D2+NA
      IF2=KB1*D1+KB2*D2+NB
      IF3=KC1*D1+KC2*D2+NC
*SECTION 5 -OUTPUT CHARACTERISTICS
PREPAR TIME,YAW
PRTPLOT YAW
LABEL  S3-LAT. DYNAMICS
TIMER FINTIM=40.0,DELT=0.02,PRDEL=0.2
END
STOP
ENDJOB
```

```
*THIS PROGRAM SIMULATES THE DYNAMICS OF A SURFACE SHIP.
*THE EQUATIONS OF MOTION ARE TO BE IN THE FORM:
*(AAAS3+BAAS2+GAAS+DAA)A+(ABAS3+BBAS2+GBAS+DBA)B+
*(ACAS3+BCAS2+GCAS+DCA)C=KA1*D1+KA2*D2+NA
*(AABS3+BABS2+GABS+DAB)A+(ABBS3+BBBS2+GBBS+DBB)B+
*(ACBS3+BCBS2+GCBS+DCB)C=KB1*D1+KB2*D2+NB
*(AACS3+BACS2+GACS+DAC)A+(ABCS3+BBCS2+GBCS+DBC)B+
*(ACCS3+BCCS2+GCCS+DCC)C=KC1*D1+KC2*D2+NC
*A,BAND C ARE THE VARIABLES.
*D1,D2 ARE THE DEFLECTIONS OF THE RUDDER(S).
*NA,NB,NC ARE TERMS IN WHICH ANY EXTERNAL FORCES OR MOMENTS,
*OR NONLINEAR TERMS CAN BE INCLUDED.
*AAB,BAB...,KA1...MUST BE DEFINED IN SECTION 2 AS FUNCTIONS
*OF THE HYDRODYNAMIC COEFFICIENTS,THE VALUES OF WHICH ARE
*INTRODUCED IN SECTION 1.
*NO ORDER IS REQUIRED.
*IN SECTION 3 THE VARIABLES ARE DEFINED,E.G. YAW=B.
*THE FIRST AND SECOND DERIVATIVES OF THE VARIABLES ARE:
*ADOT,BDOT,CDOT,ADDOT,BDDOT,CDDOT.
*IF THE REQUIRED SOLUTION INVOLVES TWO EQUATIONS,SET ACC=1.,
*THE SOLUTION WILL BE IN TERMS OF A AND B.
*UNDEFINED TERMS ARE SET AUTOMATICALLY TO ZERO,UP
*TO A MAXIMUM OF 85.
*SECTION 4 IS THE PROGRAMMED SIMULATION.
*SECTION 1 -COEFFICIENTS FOR A PARTICULAR SHIP
PARAM K=0.78137
PARAM KT=0.88835
PARAM M=0.0045
PARAM IZ=0.0003
PARAM NR=-0.0012
PARAM NRD=-0.0002
PARAM NV=-0.0012
PARAM NVD=-0.0001
PARAM KB1=-0.00084
PARAM YR=0.004
PARAM YRD=-0.0002
PARAM YV=-0.0063
PARAM YVD=-0.0025
PARAM KA1=0.0019
PARAM XU=-0.0012
PARAM XUD=-0.00036
PARAM KC1=-0.0011
*SECTION 2 -PARAMETERS CALCULATIONS
       AAA=M-YVD
       BAA=-YV+10.0*(M-YVD)
       ABA=-YRD
       BBA=M-YR-10.0*KA1*KT
       AAB=-NVD
       BAB=-NV-10.0*NVD
       ABB=IZ-NRD
       BBB=-NR+10.0*(IZ-NRD)
       BCC=-XU+10.0*(M-XUD)
       ACC=M-XUD
       NC=-10.0*XU
       GAA=-10.0*YV
       GBA=10.0*(M-YR)-10.0*KA1*KT
       DBA=-10.0*KA1*K
       GAB=-10.0*NV
       GBB=-10.0*NR-10.0*KB1*KT
       DBB=-10.0*KB1*K
       GBC=-10.0*KC1*KT
       DBC=-10.0*KC1*K
       GCC=-10.0*XU
       COFAA=ABB*ACC-ACB*ABC
```

```
      COFAB=-(ABA*ACC-ACA*ABC)
      COFAC=ABA*ACB-ABB*ACA
      COFBA=-(AAB*ACC-ACB*AAC)
      COFBB=AAA*ACC-ACA*AAC
      COFBC=-(AAA*ACB-ACA*AAB)
      COFCA=AAB*ABC-ABB*AAC
      COFCB=-(AAA*ABC-ABA*AAC)
      COFCC=AAA*ABB-ABA*AAB
      S1=AAA*ABB*ACC+AAB*ABC*ACA+AAC*ACB*ABA
      S2=ACA*ABB*AAC+ACB*ABC*AAA+ACC*AAB*ABA
      DEL=S1-S2
*SECTION 3 -PHYSICAL DEFINITIONS
      YAW=B
      SWAY=Y
      SURGE=X
*SECTION 4 -PROGRAMMED SIMULATION
      ADDDOT=(COFAA*I1+COFAB*I2+COFAC*I3)/DEL
      ADDOT=INTGRL(0.,ADDDOT)
      ADOT=INTGRL(0.,ADDOT)
      A=INTGRL(0.,ADOT)
      BDDDOT=(COFBA*I1+COFBB*I2+COFBC*I3)/DEL
      BDDOT=INTGRL(0.,BDDDOT)
      BDOT=INTGRL(0.1,BDDOT)
      B=INTGRL(0.2,BDOT)
      CDDDOT=(COFCA*I1+COFCB*I2+COFCC*I3)/DEL
      CDDOT=INTGRL(0.,CDDDOT)
      CDOT=INTGRL(0.,CDDOT)
      C=INTGRL(0.,CDOT)
      I1=-BAA*ADDDOT-GAA*ADOT-BBA*BDDOT-GBA*BDOT+IF1-DAA*A-DBA*B
      I2=-BAB*ADDDOT-GAB*ADOT-BBB*BDDOT-GBB*BDOT+IF2-DAB*A-DBB*B
      I3=-BBC*BDDOT-GBC*BDOT-BCC*CDDOT-GCC*CDOT+IF3-DCC*C-DBC*B
      IF1=0.0
      IF2=0.0
      IF3=NC
*SECTION 5 -OUTPUT CHARACTERISTICS
PREPAR TIME,YAW
PRTPLOT YAW
LABEL  S3-LAT. DYNAMICS
TIMER FINTIM=40.0,DELT=0.02,PRDEL=0.2
END
STOP
ENDJOB
```

COMPUTER PROGRAM III

```
*THIS PROGRAM SIMULATES THE DYNAMICS OF A SURFACE SHIP.
*THE EQUATIONS OF MOTION ARE TO BE IN THE FORM:
*(AAAS3+BAAS2+GAAS+DAA)A+(ABAS3+BBAS2+GBAS+DBA)B+
*(ACAS3+BCAS2+GCAS+DCA)C=KA1*D1+KA2*D2+NA
*(AABS3+BABS2+GABS+DAB)A+(ABBS3+BBBS2+GBBS+DBB)B+
*(ACBS3+BCBS2+GCBS+DCB)C=KB1*D1+KB2*D2+NB
*(AACS3+BACS2+GACS+DAC)A+(ABCS3+BBCS2+GBCS+DBC)B+
*(ACCS3+BCCS2+GCCS+DCC)C=KC1*D1+KC2*D2+NC
*A,BAND C ARE THE VARIABLES.
*D1,D2 ARE THE DEFLECTIONS OF THE RUDDER(S).
*NA,NB,NC ARE TERMS IN WHICH ANY EXTERNAL FORCES OR MOMENTS,
*OR NONLINEAR TERMS CAN BE INCLUDED.
*AAB,BAB...,KA1...MUST BE DEFINED IN SECTION 2 AS FUNCTIONS
*OF THE HYDRODYNAMIC COEFFICIENTS,THE VALUES OF WHICH ARE
*INTRODUCED IN SECTION 1.
*NO ORDER IS REQUIRED.
*IN SECTION 3 THE VARIABLES ARE DEFINED,E.G. YAW=B.
*THE FIRST AND SECOND DERIVATIVES OF THE VARIABLES ARE:
*ADOT,BDOT,CDOT,ADDOT,BDDOT,CDDOT.
*IF THE REQUIRED SOLUTION INVOLVES TWO EQUATIONS,SET ACC=1.,
*THE SOLUTION WILL BE IN TERMS OF A AND B.
*UNDEFINED TERMS ARE SET AUTOMATICALLY TO ZERO,UP
*TO A MAXIMUM OF 85.
*SECTION 4 IS THE PROGRAMMED SIMULATION.
*SECTION 1 -COEFFICIENTS FOR A PARTICULAR SHIP
PARAM D=0.1
PARAM K=0.0225
PARAM KT=0.25942
PARAM M=0.0045
PARAM IZ=0.0003
PARAM NR=-0.0012
PARAM NRD=-0.0002
PARAM NV=-0.0012
PARAM NVD=-0.0001
PARAM KB1=-0.00084
PARAM YR=0.004
PARAM YRD=-0.0002
PARAM YV=-0.0063
PARAM YVD=-0.0025
PARAM KA1=0.0019
PARAM XU=-0.0012
PARAM XUD=-0.00036
PARAM KC1=-0.0011
*SECTION 2 -PARAMETERS CALCULATIONS
      AAA=M-YVD
      BAA=-YV+10.0*(M-YVD)
      ABA=-YRD
      BBA=M-YR-10.0*YRD
      AAB=-NVD
      BAB=-NV-10.0*NVD
      ABB=IZ-NRD
      BBB=-NR+10.0*(IZ-NRD)
      BCC=-XU+10.0*(M-XUD)
      ACC=M-XUD
      NC=-10.0*XU
      GAA=-10.0*YV
      GBA=10.0*(M-YR)
      GAB=-10.0*NV
      GBB=-10.0*NR
      GCC=-10.0*XU
      COFAA=ABB*ACC-ACB*ABC
      COFAB=-(ABA*ACC-ACA*ABC)
      COFAC=ABA*ACB-ABB*ACA
      COFBA=-(AAB*ACC-ACB*AAC)
```

```
      COFBB=AAA*ACC-ACA*AAC
      COFBC=-(AAA*ACB-ACA*AAB)
      COFCA=AAB*ABC-ABB*AAC
      COFCB=-(AAA*ABC-ABA*AAC)
      COFCC=AAA*ABB-ABA*AAB
      S1=AAA*ABB*ACC+AAB*ABC*ACA+AAC*ACB*ABA
      S2=ACA*ABB*AAC+ACB*ABC*AAA+ACC*AAB*ABA
      DEL=S1-S2
*SECTION 3 -PHYSICAL DEFINITIONS
      YAW=B
      SWAY=Y
      SURGE=X
*SECTION 4 -PROGRAMMED SIMULATION
      ADDDOT=(COFAA*I1+COFAB*I2+COFAC*I3)/DEL
      ADDOT=INTGRL(0.,ADDDOT)
      ADOT=INTGRL(0.01,ADDOT)
      A=INTGRL(0.,ADOT)
      BDDDOT=(COFBA*I1+COFBB*I2+COFBC*I3)/DEL
      BDDOT=INTGRL(0.,BDDDOT)
      BDOT=INTGRL(0.,BDDOT)
      B=INTGRL(0.,BDOT)
      CDDDOT=(COFCA*I1+COFCB*I2+COFCC*I3)/DEL
      CDDOT=INTGRL(0.,CDDDOT)
      CDOT=INTGRL(0.,CDDOT)
      C=INTGRL(0.,CDOT)
      I1=-BAA*ADDOT-GAA*ADOT-BBA*BDDOT-GBA*BDOT+IF1-DAA*A-DBA*B
      I2=-BAB*ADDOT-GAB*ADOT-BBB*BDDOT-GBB*BDOT+IF2-DAB*A-DBB*B
      I3=-BBC*BDDOT-GBC*BDOT-BCC*CDDOT-GCC*CDOT+IF3-DCC*C-DBC*B
      IF1=10.0*KA1*DD
      IF2=10.0*KB1*DD
      IF3=NC+10.0*KC1*DD
      DD=K*Y+KT*YDOT
      YDOT=CDOT*SIN(YAW)+ADOT*COS(YAW)
      Y=INTGRL(0.1,YDOT)
*SECTION 5 -OUTPUT CHARACTERISTICS
PREPAR TIME,YAW
PRTPLOT YAW
LABEL  S3-LAT. DYNAMICS
TIMER FINTIM=40.0,DELT=0.02,PRDEL=0.2
END
STOP
ENDJOB
```

```
*THIS PROGRAM SIMULATES THE DYNAMICS OF A SURFACE SHIP.
*THE EQUATIONS OF MOTION ARE TO BE IN THE FORM:
*(AAAS3+BAAS2+GAAS+DAA)A+(ABAS3+BBAS2+GBAS+DBA)B+
*(ACAS3+BCAS2+GCAS+DCA)C=KA1*D1+KA2*D2+NA
*(AABS3+BABS2+GABS+DAB)A+(ABBS3+BBBS2+GBBS+DBB)B+
*(ACBS3+BCBS2+GCBS+DCB)C=KB1*D1+KB2*D2+NB
*(AACS3+BACS2+GACS+DAC)A+(ABCS3+BBCS2+GBCS+DBC)B+
*(ACCS3+BCCS2+GCCS+DCC)C=KC1*D1+KC2*D2+NC
*A,BAND C ARE THE VARIABLES.
*D1,D2 ARE THE DEFLECTIONS OF THE RUDDER(S).
*NA,NB,NC ARE TERMS IN WHICH ANY EXTERNAL FORCES OR MOMENTS,
*OR NONLINEAR TERMS CAN BE INCLUDED.
*AAB,BAB...,KA1...MUST BE DEFINED IN SECTION 2 AS FUNCTIONS
*OF THE HYDRODYNAMIC COEFFICIENTS,THE VALUES OF WHICH ARE
*INTRODUCED IN SECTION 1.
*NO ORDER IS REQUIRED.
*IN SECTION 3 THE VARIABLES ARE DEFINED,E.G. YAW=B.
*THE FIRST AND SECOND DERIVATIVES OF THE VARIABLES ARE:
*ADOT,BDOT,CDOT,ADDOT,BDDOT,CDDOT.
*IF THE REQUIRED SOLUTION INVOLVES TWO EQUATIONS,SET ACC=1.,
*THE SOLUTION WILL BE IN TERMS OF A AND B.
*UNDEFINED TERMS ARE SET AUTOMATICALLY TO ZERO,UP
*TO A MAXIMUM OF 85.
*SECTION 4 IS THE PROGRAMMED SIMULATION.
*SECTION 1 -COEFFICIENTS FOR A PARTICULAR SHIP
PARAM D=0.1
PARAM K=0.0225
PARAM KT=0.25942
PARAM M=0.0045
PARAM IZ=0.0003
PARAM NR=-0.0012
PARAM NRD=-0.0002
PARAM NV=-0.0012
PARAM NVD=-0.0001
PARAM KB1=-0.00084
PARAM YR=0.004
PARAM YRD=-0.0002
PARAM YV=-0.0063
PARAM YVD=-0.0025
PARAM KA1=0.0019
PARAM XU=-0.0012
PARAM XUD=-0.00036
PARAM KC1=-0.0011
*SECTION 2 -PARAMETERS CALCULATIONS
       AAA=M-YVD
       BAA=-YV+10.0*(M-YVD)
       ABA=-YRD
       BBA=M-YR-10.0*YRD
       AAB=-NVD
       BAB=-NV-10.0*NVD
       ABB=IZ-NRD
       BBB=-NR+10.0*(IZ-NRD)
       BCC=-XU+10.0*(M-XUD)
       ACC=M-XUD
       NC=-10.0*XU
       GAA=-10.0*YV
       GBA=10.0*(M-YR)
       GAB=-10.0*NV
       GBB=-10.0*NR
       GCC=-10.0*XU
       COFAA=ABB*ACC-ACB*ABC
       COFAB=-(ABA*ACC-ACA*ABC)
       COFAC=ABA*ACB-ABB*ACA
       COFBA=-(AAB*ACC-ACB*AAC)
```

```
        COFBB=AAA*ACC-ACA*AAC
        COFBC=-(AAA*ACB-ACA*AAB)
        COFCA=AAB*ABC-ABB*AAC
        COFCB=-(AAA*ABC-ABA*AAC)
        COFCC=AAA*ABB-ABA*AAB
        S1=AAA*ABB*ACC+AAB*ABC*ACA+AAC*ACB*ABA
        S2=ACA*ABB*AAC+ACB*ABC*AAA+ACC*AAB*ABA
        DEL=S1-S2
*SECTION 3 -PHYSICAL DEFINITIONS
        YAW=B
        SWAY=Y
        SURGE=X
*SECTION 4 -PROGRAMMED SIMULATION
        ADDDOT=(COFAA*I1+COFAB*I2+COFAC*I3)/DEL
        ADDOT=INTGRL(0.,ADDDOT)
        ADOT=INTGRL(0.,ADDOT)
        A=INTGRL(0.,ADOT)
        BDDDOT=(COFBA*I1+COFBB*I2+COFBC*I3)/DEL
        BDDOT=INTGRL(0.,BDDDOT)
        BDOT=INTGRL(0.,BDDOT)
        B=INTGRL(0.,BDOT)
        CDDDOT=(COFCA*I1+COFCB*I2+COFCC*I3)/DEL
        CDDOT=INTGRL(0.,CDDDOT)
        CDOT=INTGRL(0.,CDDOT)
        C=INTGRL(0.,CDOT)
        I1=-BAA*ADDOT-GAA*ADOT-BBA*BDDOT-GBA*BDOT+IF1-DAA*A-DBA*B
        I2=-BAB*ADDOT-GAB*ADOT-BBB*BDDOT-GBB*BDOT+IF2-DAB*A-DBB*B
        I3=-BBC*BDDOT-GBC*BDOT-BCC*CDDOT-GCC*CDOT+IF3-DCC*C-DBC*B
        IF1=10.0*KA1*DD
        IF2=10.0*KB1*DD
        IF3=NC+10.0*KC1*DD
        DD=K*(Y-D)+KT*YDOT
        YDOT=CDOT*SIN(YAW)+ADOT*COS(YAW)
        Y=INTGRL(0.,YDOT)
*SECTION 5 -OUTPUT CHARACTERISTICS
PREPAR TIME,SWAY,SURGE,YAW
PRTPLOT SWAY
LABEL  S3-LAT. DYNAMICS
TIMER FINTIM=40.0,DELT=0.02,PRDEL=0.2
END
STOP
ENDJOB
```

COMPUTER PROGRAM V

```
*THIS PROGRAM SIMULATES THE DYNAMICS OF TWO SURFACE SHIPS.
*THE EQUATIONS OF MOTION FOR EACH ARE TO BE IN THE FORM:
*(AAAS3+BAAS2+GAAS+DAA)A+(ABAS3+BBAS2+GBAS+DBA)B+
*(ACAS3+BCAS2+GCAS+DCA)C=KA1*D1+KA2*D2+NA
*(AABS3+BABS2+GABS+DAB)A+(ABBS3+BBBS2+GBBS+DBB)B+
*(ACBS3+BCBS2+GCBS+DCB)C=KB1*D1+KB2*D2+NB
*(AACS3+BACS2+GACS+DAC)A+(ABCS3+BBCS2+GBCS+DBC)B+
*(ACCS3+BCCS2+GCCS+DCC)C=KC1*D1+KC2*D2+NC
*A,BAND C ARE THE VARIABLES.
*D1,D2 ARE THE DEFLECTIONS OF THE RUDDER(S).
*NA,NB,NC ARE TERMS IN WHICH ANY EXTERNAL FORCES OR MOMENTS,
*OR NONLINEAR TERMS CAN BE INCLUDED.
*AAB,BAB...,KA1...MUST BE DEFINED IN SECTION 2 AS FUNCTIONS
*OF THE HYDRODYNAMIC COEFFICIENTS,THE VALUES OF WHICH ARE
*INTRODUCED IN SECTION 1.
*NO ORDER IS REQUIRED.
*IN SECTION 3 THE VARIABLES ARE DEFINED,E.G. YAW=B.
*THE FIRST AND SECOND DERIVATIVES OF THE VARIABLES ARE:
*ADOT,BDOT,CDOT,ADDOT,BDDOT,CDDOT.
*IF THE REQUIRED SOLUTION INVOLVES TWO EQUATIONS,SET ACC=1.,
*THE SOLUTION WILL BE IN TERMS OF A AND B.
*UNDEFINED TERMS ARE SET AUTOMATICALLY TO ZERO,UP
*TO A MAXIMUM OF 85.
*SECTION 4 IS THE PROGRAMMED SIMULATION.
*THE HYDRODYNAMIC COEFFICIENTS ARE HERE COMMON SINCE THE TWO
*SHIPS ARE ASSUMED IDENTICAL.
*SUBSCRIPT 1 REFERS TO THE REPLENISHING SHIP AND SUBSCRIPT 2
*REFERS TO THE RECEIVING SHIP.
*DDC IS THE ORDERED RUDDER ANGLE FOR COURSE CONTROL AND DDD
*IS THE ORDERED(HELM)RUDDER ANGLE FOR DISTANCE CONTROL.
*YI AND NI ARE THE INTERACTIVE FORCE AND MOMENT.
*SECTION 1 -COEFFICIENTS FOR A PARTICULAR SHIP
PARAM YI2=-0.000216
PARAM NI2=0.0000152
PARAM M=0.0045
PARAM IZ=0.0003
PARAM NR=-0.0012
PARAM NRD=-0.0002
PARAM NV=-0.0012
PARAM NVD=-0.0001
PARAM KB1=-0.00084
PARAM YR=0.004
PARAM YRD=-0.0002
PARAM YV=-0.0063
PARAM YVD=-0.0025
PARAM KA1=0.0019
PARAM XU=-0.0012
PARAM XUD=-0.00036
PARAM KC1=-0.0011
*SECTION 2 -PARAMETERS CALCULATIONS
       AAA=M-YVD
       BAA=-YV+10.0*(M-YVD)
       ABA=-YRD
       BBA=M-YR-10.0*YRD
       AAB=-NVD
       BAB=-NV-10.0*NVD
       ABB=IZ-NRD
       BBB=-NR+10.0*(IZ-NRD)
       BCC=-XU+10.0*(M-XUD)
       ACC=M-XUD
       NC=-10.0*XU
       GAA=-10.0*YV
       GBA=10.0*(M-YR)
       GAB=-10.0*NV
```

```
      GBB=-10.0*NR
      GCC=-10.0*XU
      COFAA=ABB*ACC-ACB*ABC
      COFAB=-(ABA*ACC-ACA*ABC)
      COFAC=ABA*ACB-ABB*ACA
      COFBA=-(AAB*ACC-ACB*AAC)
      COFBB=AAA*ACC-ACA*AAC
      COFBC=-(AAA*ACB-ACA*AAB)
      COFCA=AAB*ABC-ABB*AAC
      COFCB=-(AAA*ABC-ABA*AAC)
      COFCC=AAA*ABB-ABA*AAB
      S1=AAA*ABB*ACC+AAB*ABC*ACA+AAC*ACB*ABA
      S2=ACA*ABB*AAC+ACB*ABC*AAA+ACC*AAB*ABA
      DEL=S1-S2
*SECTION 3 -PHYSICAL DEFINITIONS
      YAW2=B2
      SWAY2=Y2
      SURGE2=X2
*SECTION 4 -PROGRAMMED SIMULATION
      ADDD2=(COFAA*I12+COFAB*I22+COFAC*I32)/DEL
      ADD2=INTGRL(0.,ADDD2)
      AD2=INTGRL(0.,ADD2)
      A2=INTGRL(0.,AD2)
      BDDD2=(COFBA*I12+COFBB*I22+COFBC*I32)/DEL
      BDD2=INTGRL(0.,BDDD2)
      BD2=INTGRL(0.,BDD2)
      B2=INTGRL(0.,BD2)
      CDDD2=(COFCA*I12+COFCB*I22+COFCC*I32)/DEL
      CDD2=INTGRL(0.,CDDD2)
      CD2=INTGRL(0.,CDD2)
      C2=INTGRL(0.,CD2)
      YDOT2=CD2*SIN(YAW2)+AD2*COS(YAW2)
      Y2=INTGRL(0.,YDOT2)
      XDOT2=CD2*COS(YAW2)-AD2*SIN(YAW2)
      X2=INTGRL(0.,XDOT2)
      I12=-BAA*ADD2-GAA*AD2-BBA*BDD2-GBA*BD2+IF12
      I22=-BAB*ADD2-GAB*AD2-BBB*BDD2-GBB*BD2+IF22
      I32=-BCC*CDD2-GCC*CD2+IF32
      IF12=10.0*KA1*DD2+YI2
      IF22=10.0*KB1*DD2+NI2
      IF32=10.0*KC1*DD2+NC
*SECTION 5 -OUTPUT CHARACTERISTICS
PRTPLOT YAW2
PRTPLOT SWAY2
LABEL   S3-LAT. DYNAMICS
TIMER FINTIM=40.0,DELT=0.02,PRDEL=0.2
END
STOP
ENDJOB
```

```
*THIS PROGRAM SIMULATES THE DYNAMICS OF TWO SURFACE SHIPS.
*THE EQUATIONS OF MOTION FOR EACH ARE TO BE IN THE FORM:
*(AAAS3+BAAS2+GAAS+DAA)A+(ABAS3+BBAS2+GBAS+DBA)B+
*(ACAS3+BCAS2+GCAS+DCA)C=KA1*D1+KA2*D2+NA
*(AABS3+BABS2+GABS+DAB)A+(ABBS3+BBBS2+GBBS+DBB)B+
*(ACBS3+BCBS2+GCBS+DCB)C=KB1*D1+KB2*D2+NB
*(AACS3+BACS2+GACS+DAC)A+(ABCS3+BBCS2+GBCS+DBC)B+
*(ACCS3+BCCS2+GCCS+DCC)C=KC1*D1+KC2*D2+NC
*A,BAND C ARE THE VARIABLES.
*D1,D2 ARE THE DEFLECTIONS OF THE RUDDER(S).
*NA,NB,NC ARE TERMS IN WHICH ANY EXTERNAL FORCES OR MOMENTS,
*OR NONLINEAR TERMS CAN BE INCLUDED.
*AAB,BAB...,KA1...MUST BE DEFINED IN SECTION 2 AS FUNCTIONS
*OF THE HYDRODYNAMIC COEFFICIENTS,THE VALUES OF WHICH ARE
*INTRODUCED IN SECTION 1.
*NO ORDER IS REQUIRED.
*IN SECTION 3 THE VARIABLES ARE DEFINED,E.G. YAW=B.
*THE FIRST AND SECOND DERIVATIVES OF THE VARIABLES ARE:
*ADOT,BDOT,CDOT,ADDOT,BDDOT,CDDOT.
*IF THE REQUIRED SOLUTION INVOLVES TWO EQUATIONS,SET ACC=1.,
*THE SOLUTION WILL BE IN TERMS OF A AND B.
*UNDEFINED TERMS ARE SET AUTOMATICALLY TO ZERO,UP
*TO A MAXIMUM OF 85.
*SECTION 4 IS THE PROGRAMMED SIMULATION.
*THE HYDRODYNAMIC COEFFICIENTS ARE HERE COMMON SINCE THE TWO
*SHIPS ARE ASSUMED IDENTICAL.
*SUBSCRIPT 1 REFERS TO THE REPLENISHING SHIP AND SUBSCRIPT 2
*REFERS TO THE RECEIVING SHIP.
*DDC IS THE ORDERED RUDDER ANGLE FOR COURSE CONTROL AND DDD
*IS THE ORDERED(HELM)RUDDER ANGLE FOR DISTANCE CONTROL.
*YI AND NI ARE THE INTERACTIVE FORCE AND MOMENT.
*SECTION 1 -COEFFICIENTS FOR A PARTICULAR SHIP
PARAM K1=2.34
PARAM KT1=2.73
PARAM K2=2.35
PARAM KT2=2.75
PARAM KP2=1.1
PARAM KTP2=1.3
PARAM NI1=-0.0000152
PARAM YI1=0.000216
PARAM NI2=0.0000152
PARAM YI2=-0.000216
PARAM M=0.0045
PARAM IZ=0.0003
PARAM NR=-0.0012
PARAM NRD=-0.0002
PARAM NV=-0.0012
PARAM NVD=-0.0001
PARAM KB1=-0.00084
PARAM YR=0.004
PARAM YRD=-0.0002
PARAM YV=-0.0063
PARAM YVD=-0.0025
PARAM KA1=0.0019
PARAM XU=-0.0012
PARAM XUD=-0.00036
PARAM KC1=-0.0011
*SECTION 2 -PARAMETERS CALCULATIONS
      AAA=M-YVD
      BAA=-YV+10.0*(M-YVD)
      ABA=-YRD
      BBA=M-YR-10.0*YRD
      AAB=-NVD
      BAB=-NV-10.0*NVD
```

```
      ABB=IZ-NRD
      BBB=-NR+10.0*(IZ-NRD)
      BCC=-XU+10.0*(M-XUD)
      ACC=M-XUD
      NC=-10.0*XU
      GAA=-10.0*YV
      GBA=10.0*(M-YR)
      GAB=-10.0*NV
      GBB=-10.0*NR
      GCC=-10.0*XU
      COFAA=ABB*ACC-ACB*ABC
      COFAB=-(ABA*ACC-ACA*ABC)
      COFAC=ABA*ACB-ABB*ACA
      COFBA=-(AAB*ACC-ACB*AAC)
      COFBB=AAA*ACC-ACA*AAC
      COFBC=-(AAA*ACB-ACA*AAB)
      COFCA=AAB*ABC-ABB*AAC
      COFCB=-(AAA*ABC-ABA*AAC)
      COFCC=AAA*ABB-ABA*AAB
      S1=AAA*ABB*ACC+AAB*ABC*ACA+AAC*ACB*ABA
      S2=ACA*ABB*AAC+ACB*ABC*AAA+ACC*AAB*ABA
      DEL=S1-S2
*SECTION 3 -PHYSICAL DEFINITIONS
      YAW1=B1
      SWAY1=Y1
      SURGE1=X1
      YAW2=B2
      SWAY2=Y2
      SURGE2=X2
*SECTION 4 -PROGRAMMED SIMULATION
      ADDD1=(COFAA*I11+COFAB*I21+COFAC*I31)/DEL
      ADD1=INTGRL(0.,ADDD1)
      AD1=INTGRL(0.,ADD1)
      A1=INTGRL(0.,AD1)
      BDDD1=(COFBA*I11+COFBB*I21+COFBC*I31)/DEL
      BDD1=INTGRL(0.,BDDD1)
      BD1=INTGRL(0.,BDD1)
      B1=INTGRL(0.,BD1)
      CDDD1=(COFCA*I11+COFCB*I21+COFCC*I31)/DEL
      CDD1=INTGRL(0.,CDDD1)
      CD1=INTGRL(0.,CDD1)
      C1=INTGRL(0.,CD1)
      YDOT1=CD1*SIN(YAW1)+AD1*COS(YAW1)
      Y1=INTGRL(0.,YDOT1)
      XDOT1=CD1*COS(YAW1)-AD1*SIN(YAW1)
      X1=INTGRL(0.,XDOT1)
      I11=-BAA*ADD1-GAA*AD1-BBA*BDD1-GBA*BD1+IF11
      I21=-BAB*ADD1-GAB*AD1-BBB*BDD1-GBB*BD1+IF21
      I31=-BCC*CDD1-GCC*CD1+IF31
      IF11=10.0*KA1*DD1+YI1
      IF21=10.0*KB1*DD1+NI1
      IF31=10.0*KC1*DD1+NC
      DDC1=K1*B1+KT1*BD1
      DD1=DDC1+DDD1
      ADDD2=(COFAA*I12+COFAB*I22+COFAC*I32)/DEL
      ADD2=INTGRL(0.,ADDD2)
      AD2=INTGRL(0.,ADD2)
      A2=INTGRL(0.,AD2)
      BDDD2=(COFBA*I12+COFBB*I22+COFBC*I32)/DEL
      BDD2=INTGRL(0.,BDDD2)
      BD2=INTGRL(0.,BDD2)
      B2=INTGRL(0.,BD2)
      CDDD2=(COFCA*I12+COFCB*I22+COFCC*I32)/DEL
      CDD2=INTGRL(0.,CDDD2)
      CD2=INTGRL(0.,CDD2)
      C2=INTGRL(0.,CD2)
      YDOT2=CD2*SIN(YAW2)+AD2*COS(YAW2)
      Y2=INTGRL(0.,YDOT2)
      XDOT2=CD2*COS(YAW2)-AD2*SIN(YAW2)
      X2=INTGRL(0.,XDOT2)
      I12=-BAA*ADD2-GAA*AD2-BBA*BDD2-GBA*BD2+IF12
      I22=-BAB*ADD2-GAB*AD2-BBB*BDD2-GBB*BD2+IF22
```

```
        I32=-BCC*CDD2-GCC*CD2+IF32
        IF12=10.0*KA1*DD2+YI2
        IF22=10.0*KB1*DD2+NI2
        IF32=10.0*KC1*DD2+NC
        D=Y2-Y1
        DDOT=YDOT2-YDOT1
        DDC2=K2*B2+KT2*BD2
        DDD2=KP2*D+KTP2*DDOT
        DD2=DDD2+DDC2
*SECTION 5 -OUTPUT CHARACTERISTICS
PRTPLOT SWAY1
PRTPLOT YAW1
PRTPLOT SURGE1
PRTPLOT SWAY2
PRTPLOT YAW2
PRTPLOT SURGE2
LABEL  S3-LAT. DYNAMICS
TIMER FINTIM=40.0,DELT=0.02,PRDEL=0.2
END
STOP
ENDJOB
```

COMPUTER PROGRAM VII

```
*THIS PROGRAM SIMULATES THE DYNAMICS OF TWO SURFACE SHIPS.
*THE EQUATIONS OF MOTION FOR EACH ARE TO BE IN THE FORM:
*(AAAS3+BAAS2+GAAS+DAA)A+(ABAS3+BBAS2+GBAS+DBA)B+
*(ACAS3+BCAS2+GCAS+DCA)C=KA1*D1+KA2*D2+NA
*(AABS3+BABS2+GABS+DAB)A+(ABBS3+BBBS2+GBBS+DBB)B+
*(ACBS3+BCBS2+GCBS+DCB)C=KB1*D1+KB2*D2+NB
*(AACS3+BACS2+GACS+DAC)A+(ABCS3+BBCS2+GBCS+DBC)B+
*(ACCS3+BCCS2+GCCS+DCC)C=KC1*D1+KC2*D2+NC
*A,BAND C ARE THE VARIABLES.
*D1,D2 ARE THE DEFLECTIONS OF THE RUDDER(S).
*NA,NB,NC ARE TERMS IN WHICH ANY EXTERNAL FORCES OR MOMENTS,
*OR NONLINEAR TERMS CAN BE INCLUDED.
*AAB,BAB...,KA1...MUST BE DEFINED IN SECTION 2 AS FUNCTIONS
*OF THE HYDRODYNAMIC COEFFICIENTS,THE VALUES OF WHICH ARE
*INTRODUCED IN SECTION 1.
*NO ORDER IS REQUIRED.
*IN SECTION 3 THE VARIABLES ARE DEFINED,E.G. YAW=B.
*THE FIRST AND SECOND DERIVATIVES OF THE VARIABLES ARE:
*ADOT,BDOT,CDOT,ADDOT,BDDOT,CDDOT.
*IF THE REQUIRED SOLUTION INVOLVES TWO EQUATIONS,SET ACC=1.,
*THE SOLUTION WILL BE IN TERMS OF A AND B.
*UNDEFINED TERMS ARE SET AUTOMATICALLY TO ZERO,UP
*TO A MAXIMUM OF 85.
*SECTION 4 IS THE PROGRAMMED SIMULATION.
*THE HYDRODYNAMIC COEFFICIENTS ARE HERE COMMON SINCE THE TWO
*SHIPS ARE ASSUMED IDENTICAL.
*SUBSCRIPT 1 REFERS TO THE REPLENISHING SHIP AND SUBSCRIPT 2
*REFERS TO THE RECEIVING SHIP.
*DDC IS THE ORDERED RUDDER ANGLE FOR COURSE CONTROL AND DDD
*IS THE ORDERED(HELM)RUDDER ANGLE FOR DISTANCE CONTROL.
*YI AND NI ARE THE INTERACTIVE FORCE AND MOMENT.
*SECTION 1 -COEFFICIENTS FOR A PARTICULAR SHIP
PARAM K1=2.3
PARAM KT1=2.7
PARAM K2=2.35
PARAM KT2=2.75
PARAM KP2=1.1
PARAM KTP2=1.3
PARAM NI1=-0.0000152
PARAM YI1=0.000216
PARAM NI2=0.0000152
PARAM YI2=-0.000216
PARAM M=0.0045
PARAM IZ=0.0003
PARAM NR=-0.0012
PARAM NRD=-0.0002
PARAM NV=-0.0012
PARAM NVD=-0.0001
PARAM KB1=-0.00084
PARAM YR=0.004
PARAM YRD=-0.0002
PARAM YV=-0.0063
PARAM YVD=-0.0025
PARAM KA1=0.0019
PARAM XU=-0.0012
PARAM XUD=-0.00036
PARAM KC1=-0.0011
*SECTION 2 -PARAMETERS CALCULATIONS
       AAA=M-YVD
       BAA=-YV+10.0*(M-YVD)
       ABA=-YRD
       BBA=M-YR-10.0*YRD
       AAB=-NVD
       BAB=-NV-10.0*NVD
```

```
      ABB=IZ-NRD
      BBB=-NR+10.0*(IZ-NRD)
      BCC=-XU+10.0*(M-XUD)
      ACC=M-XUD
      NC=-10.0*XU
      GAA=-10.0*YV
      GBA=10.0*(M-YR)
      GAB=-10.0*NV
      GBB=-10.0*NR
      GCC=-10.0*XU
      COFAA=ABB*ACC-ACB*ABC
      COFAB=-(ABA*ACC-ACA*ABC)
      COFAC=ABA*ACB-ABB*ACA
      COFBA=-(AAB*ACC-ACB*AAC)
      COFBB=AAA*ACC-ACA*AAC
      COFBC=-(AAA*ACB-ACA*AAB)
      COFCA=AAB*ABC-ABB*AAC
      COFCB=-(AAA*ABC-ABA*AAC)
      COFCC=AAA*ABB-ABA*AAB
      S1=AAA*ABB*ACC+AAB*ABC*ACA+AAC*ACB*ABA
      S2=ACA*ABB*AAC+ACB*ABC*AAA+ACC*AAB*ABA
      DEL=S1-S2
*SECTION 3 -PHYSICAL DEFINITIONS
      YAW1=B1
      SWAY1=Y1
      SURGE1=X1
      YAW2=B2
      SWAY2=Y2
      SURGE2=X2
*SECTION 4 -PROGRAMMED SIMULATION
      ADDD1=(COFAA*I11+COFAB*I21+COFAC*I31)/DEL
      ADD1=INTGRL(0.,ADDD1)
      AD1=INTGRL(0.,ADD1)
      A1=INTGRL(0.,AD1)
      BDDD1=(COFBA*I11+COFBB*I21+COFBC*I31)/DEL
      BDD1=INTGRL(0.,BDDD1)
      BD1=INTGRL(0.,BDD1)
      B1=INTGRL(0.,BD1)
      CDDD1=(COFCA*I11+COFCB*I21+COFCC*I31)/DEL
      CDD1=INTGRL(0.,CDDD1)
      CD1=INTGRL(0.,CDD1)
      C1=INTGRL(0.,CD1)
      YDOT1=CD1*SIN(YAW1)+AD1*COS(YAW1)
      Y1=INTGRL(0.,YDOT1)
      XDOT1=CD1*COS(YAW1)-AD1*SIN(YAW1)
      X1=INTGRL(0.,XDOT1)
      I11=-BAA*ADD1-GAA*AD1-BBA*BDD1-GBA*BD1+IF11
      I21=-BAB*ADD1-GAB*AD1-BBB*BDD1-GBB*BD1+IF21
      I31=-BCC*CDD1-GCC*CD1+IF31
      IF11=10.0*KA1*DD1+YI1
      IF21=10.0*KB1*DD1+NI1
      IF31=10.0*KC1*DD1+NC
      DDC1=K1*B1+KT1*BD1
      DD1=DDC1+DDD1
      ADDD2=(COFAA*I12+COFAB*I22+COFAC*I32)/DEL
      ADD2=INTGRL(0.,ADDD2)
      AD2=INTGRL(0.,ADD2)
      A2=INTGRL(0.,AD2)
      BDDD2=(COFBA*I12+COFBB*I22+COFBC*I32)/DEL
      BDD2=INTGRL(0.,BDDD2)
      BD2=INTGRL(0.,BDD2)
      B2=INTGRL(0.,BD2)
      CDDD2=(COFCA*I12+COFCB*I22+COFCC*I32)/DEL
      CDD2=INTGRL(0.,CDDD2)
      CD2=INTGRL(0.,CDD2)
      C2=INTGRL(0.,CD2)
      YDOT2=CD2*SIN(YAW2)+AD2*COS(YAW2)
      Y2=INTGRL(0.,YDOT2)
      XDOT2=CD2*COS(YAW2)-AD2*SIN(YAW2)
      X2=INTGRL(0.,XDOT2)
      I12=-BAA*ADD2-GAA*AD2-BBA*BDD2-GBA*BD2+IF12
      I22=-BAB*ADD2-GAB*AD2-BBB*BDD2-GBB*BD2+IF22
```

```
      I32=-BCC*CDD2-GCC*CD2+IF32
      IF12=10.0*KA1*DD2+YI2
      IF22=10.0*KB1*DD2+NI2
      IF32=10.0*KC1*DD2+NC
      D=Y2-Y1
      DDOT=YDOT2-YDOT1
      DDC2=K2*B2+KT2*BD2
      DDD2=KP2*D+KTP2*DDOT
      DD2=DDD2+DDC2
*SECTION 5 -OUTPUT CHARACTERISTICS
PRTPLOT SWAY1
PRTPLOT YAW1
PRTPLOT SURGE1
PRTPLOT SWAY2
PRTPLOT YAW2
PRTPLOT SURGE2
LABEL   S3-LAT. DYNAMICS
TIMER FINTIM=40.0,DELT=0.02,PRDEL=0.2
END
STOP
ENDJOB
```

COMPUTER PROGRAM VIII

```
*THIS PROGRAM SIMULATES THE DYNAMICS OF TWO SURFACE SHIPS.
*THE EQUATIONS OF MOTION FOR EACH ARE TO BE IN THE FORM:
*(AAAS3+BAAS2+GAAS+DAA)A+(ABAS3+BBAS2+GBAS+DBA)B+
*(ACAS3+BCAS2+GCAS+DCA)C=KA1*D1+KA2*D2+NA
*(AABS3+BABS2+GABS+DAB)A+(ABBS3+BBBS2+GBBS+DBB)B+
*(ACBS3+BCBS2+GCBS+DCB)C=KB1*D1+KB2*D2+NB
*(AACS3+BACS2+GACS+DAC)A+(ABCS3+BBCS2+GBCS+DBC)B+
*(ACCS3+BCCS2+GCCS+DCC)C=KC1*D1+KC2*D2+NC
*A,BAND C ARE THE VARIABLES.
*D1,D2 ARE THE DEFLECTIONS OF THE RUDDER(S).
*NA,NB,NC ARE TERMS IN WHICH ANY EXTERNAL FORCES OR MOMENTS,
*OR NONLINEAR TERMS CAN BE INCLUDED.
*AAB,BAB...,KA1...MUST BE DEFINED IN SECTION 2 AS FUNCTIONS
*OF THE HYDRODYNAMIC COEFFICIENTS,THE VALUES OF WHICH ARE
*INTRODUCED IN SECTION 1.
*NO ORDER IS REQUIRED.
*IN SECTION 3 THE VARIABLES ARE DEFINED,E.G. YAW=B.
*THE FIRST AND SECOND DERIVATIVES OF THE VARIABLES ARE:
*ADOT,BDOT,CDOT,ADDOT,BDDOT,CDDOT.
*IF THE REQUIRED SOLUTION INVOLVES TWO EQUATIONS,SET ACC=1.,
*THE SOLUTION WILL BE IN TERMS OF A AND B.
*UNDEFINED TERMS ARE SET AUTOMATICALLY TO ZERO,UP
*TO A MAXIMUM OF 85.
*SECTION 4 IS THE PROGRAMMED SIMULATION.
*THE HYDRODYNAMIC COEFFICIENTS ARE HERE COMMON SINCE THE TWO
*SHIPS ARE ASSUMED IDENTICAL.
*SUBSCRIPT 1 REFERS TO THE REPLENISHING SHIP AND SUBSCRIPT 2
*REFERS TO THE RECEIVING SHIP.
*DDC IS THE ORDERED RUDDER ANGLE FOR COURSE CONTROL AND DDD
*IS THE ORDERED(HELM)RUDDER ANGLE FOR DISTANCE CONTROL.
*YI AND NI ARE THE INTERACTIVE FORCE AND MOMENT.
*SECTION 1 -COEFFICIENTS FOR A PARTICULAR SHIP
PARAM K1=2.35
PARAM KT1=2.75
PARAM KP1=1.1
PARAM KTP1=1.3
PARAM K2=2.35
PARAM KT2=2.75
PARAM KP2=1.1
PARAM KTP2=1.3
PARAM NI1=-0.0000152
PARAM YI1=0.000216
PARAM NI2=0.0000152
PARAM YI2=-0.000216
PARAM M=0.0045
PARAM IZ=0.0003
PARAM NR=-0.0012
PARAM NRD=-0.0002
PARAM NV=-0.0012
PARAM NVD=-0.0001
PARAM KB1=-0.00084
PARAM YR=0.004
PARAM YRD=-0.0002
PARAM YV=-0.0063
PARAM YVD=-0.0025
PARAM KA1=0.0019
PARAM XU=-0.0012
PARAM XUD=-0.00036
PARAM KC1=-0.0011
*SECTION 2 -PARAMETERS CALCULATIONS
      AAA=M-YVD
      BAA=-YV+10.0*(M-YVD)
      ABA=-YRD
      BBA=M-YR-10.0*YRD
```

```
      AAB=-NVD
      BAB=-NV-10.0*NVD
      ABB=IZ-NRD
      BBB=-NR+10.0*(IZ-NRD)
      BCC=-XU+10.0*(M-XUD)
      ACC=M-XUD
      NC=-10.0*XU
      GAA=-10.0*YV
      GBA=10.0*(M-YR)
      GAB=-10.0*NV
      GBB=-10.0*NR
      GCC=-10.0*XU
      COFAA=ABB*ACC-ACB*ABC
      COFAB=-(ABA*ACC-ACA*ABC)
      COFAC=ABA*ACB-ABB*ACA
      COFBA=-(AAB*ACC-ACB*AAC)
      COFBB=AAA*ACC-ACA*AAC
      COFBC=-(AAA*ACB-ACA*AAB)
      COFCA=AAB*ABC-ABB*AAC
      COFCB=-(AAA*ABC-ABA*AAC)
      COFCC=AAA*ABB-ABA*AAB
      S1=AAA*ABB*ACC+AAB*ABC*ACA+AAC*ACB*ABA
      S2=ACA*ABB*AAC+ACB*ABC*AAA+ACC*AAB*ABA
      DEL=S1-S2
*SECTION 3 -PHYSICAL DEFINITIONS
      YAW1=B1
      SWAY1=Y1
      SURGE1=X1
      YAW2=B2
      SWAY2=Y2
      SURGE2=X2
*SECTION 4 -PROGRAMMED SIMULATION
      ADDD1=(COFAA*I11+COFAB*I21+COFAC*I31)/DEL
      ADD1=INTGRL(0.,ADDD1)
      AD1=INTGRL(0.,ADD1)
      A1=INTGRL(0.,AD1)
      BDDD1=(COFBA*I11+COFBB*I21+COFBC*I31)/DEL
      BDD1=INTGRL(0.,BDDD1)
      BD1=INTGRL(0.,BDD1)
      B1=INTGRL(0.,BD1)
      CDDD1=(COFCA*I11+COFCB*I21+COFCC*I31)/DEL
      CDD1=INTGRL(0.,CDDD1)
      CD1=INTGRL(0.,CDD1)
      C1=INTGRL(0.,CD1)
      YDOT1=CD1*SIN(YAW1)+AD1*COS(YAW1)
      Y1=INTGRL(0.,YDOT1)
      XDOT1=CD1*COS(YAW1)-AD1*SIN(YAW1)
      X1=INTGRL(0.,XDOT1)
      I11=-BAA*ADD1-GAA*AD1-BBA*BDD1-GBA*BD1+IF11
      I21=-BAB*ADD1-GAB*AD1-BBB*BDD1-GBB*BD1+IF21
      I31=-BCC*CDD1-GCC*CD1+IF31
      IF11=10.0*KA1*DD1+YI1
      IF21=10.0*KB1*DD1+NI1
      IF31=10.0*KC1*DD1+NC
      DDC1=K1*B1+KT1*BD1
      DDD1=-KP1*D-KTP1*DDOT
      DD1=DDC1+DDD1
      ADDD2=(COFAA*I12+COFAB*I22+COFAC*I32)/DEL
      ADD2=INTGRL(0.,ADDD2)
      AD2=INTGRL(0.,ADD2)
      A2=INTGRL(0.,AD2)
      BDDD2=(COFBA*I12+COFBB*I22+COFBC*I32)/DEL
      BDD2=INTGRL(0.,BDDD2)
      BD2=INTGRL(0.,BDD2)
      B2=INTGRL(0.,BD2)
      CDDD2=(COFCA*I12+COFCB*I22+COFCC*I32)/DEL
      CDD2=INTGRL(0.,CDDD2)
      CD2=INTGRL(0.,CDD2)
      C2=INTGRL(0.,CD2)
      YDOT2=CD2*SIN(YAW2)+AD2*COS(YAW2)
      Y2=INTGRL(0.,YDOT2)
      XDOT2=CD2*COS(YAW2)-AD2*SIN(YAW2)
```

```
      X2=INTGRL(0.,XDOT2)
      I12=-BAA*ADD2-GAA*AD2-BBA*BDD2-GBA*BD2+IF12
      I22=-BAB*ADD2-GAB*AD2-BBB*BDD2-GBB*BD2+IF22
      I32=-BCC*CDD2-GCC*CD2+IF32
      IF12=10.0*KA1*DD2+YI2
      IF22=10.0*KB1*DD2+NI2
      IF32=10.0*KC1*DD2+NC
      D=Y2-Y1
      DDOT=YDOT2-YDOT1
      DDC2=K2*B2+KT2*BD2
      DDD2=KP2*D+KTP2*DDOT
      DD2=DDD2+DDC2
*SECTION 5 -OUTPUT CHARACTERISTICS
PRTPLOT SWAY1
PRTPLOT YAW1
PRTPLOT SURGE1
PRTPLOT SWAY2
PRTPLOT YAW2
PRTPLOT SURGE2
LABEL   S3-LAT. DYNAMICS
TIMER FINTIM=40.0,DELT=0.02,PRDEL=0.2
END
STOP
ENDJOB
```

LIST OF REFERENCES

1. Taylor, D. W., Some Model Experiments on Suction of Vessels, Transactions, Society of Naval Architects and Mechanical Engineers, 1909.

2. Silverstein, B. L., Linearized Theory of the Interaction of Ships, University of California, Institute of Engineering Research, May 1957.

3. DTMB Report 1461, Interaction Effects Between Ships Close Aboard in Deep Water, by R. N. Newton, p. 2-19, October 1960.

4. Abcowitz, A. M., Stability and Motion Control of Ocean Vehicles, p. 35, p. I-92, The MIT Press, 1969.

5. Mandel, P., and others, Principles of Naval Architecture, p. 468, Society of Naval Architects and Marine Engineers, 1967.

INITIAL DISTRIBUTION LIST

		No. Copies
1.	Defense Documentation Center Cameron Station Alexandria, Virginia 22314	2
2.	Library, Code 0212 Naval Postgraduate School Monterey, California 93940	2
3.	Professor George J. Thaler, 52Tr Department of Electrical Engineering Naval Postgraduate School Monterey, California 93940	6
4.	Hellenic Navy Command Paparigopoulou 2 Athens, Greece	1
5.	LT Theodore Sarzetakis, H.N. H. S. Sfendoni Hellenic Navy Command Paparigopoulou 2 Athens, Greece	1
6.	Samuel H. Brown NSRDL Annapolis, Maryland	1
7.	Larry Puckett NSRDL Annapolis, Maryland	1
8.	Walt Blumberg NSRDL Annapolis, Maryland	1
9.	Professor M. L. Wilcox, Code 52Tx Department of Electrical Engineering Naval Postgraduate School Monterey, California 93940	1
10.	Professor A. Gerba, Code 52Gz Department of Electrical Engineering Naval Postgraduate School Monterey, California 93940	1

Unclassified
Security Classification

DOCUMENT CONTROL DATA - R & D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1. ORIGINATING ACTIVITY *(Corporate author)*
Naval Postgraduate School
Monterey, California 93940

2a. REPORT SECURITY CLASSIFICATION
Unclassified

2b. GROUP

3. REPORT TITLE
MANEUVERING CONTROL OF REPLENISHMENT AT SEA

4. DESCRIPTIVE NOTES *(Type of report and, inclusive dates)*
Master's Thesis; September 1972

5. AUTHOR(S) *(First name, middle initial, last name)*
Theodoros Sarzetakis
Lieutenant, Hellenic Navy

6. REPORT DATE	7a. TOTAL NO. OF PAGES	7b. NO. OF REFS
September 1972	111	5

8a. CONTRACT OR GRANT NO	9a. ORIGINATOR'S REPORT NUMBER(S)
b. PROJECT NO.	
c.	9b. OTHER REPORT NO(S) *(Any other numbers that may be assigned this report)*
d.	

10. DISTRIBUTION STATEMENT
Approved for public release; distribution unlimited.

11. SUPPLEMENTARY NOTES	12. SPONSORING MILITARY ACTIVITY
	Naval Postgraduate School Monterey, California 93940

13. ABSTRACT

An investigation of the maneuvering control of ships involved in the replenishment at sea operation under calm water conditions is carried out.

The linearized differential equations of motion of a vessel in the horizontal plane are established and implemented for the formation of computer programs, useful for the study of the behavior and stability of the ship with and without the influence of control surfaces (rudders).

Three methods of controlling automatically the maneuvering of two ships, in replenishment at sea, under the influence of interactive forces and moments, based on the classical feedback control theory are presented, compared and conclusions are finally drawn about the efficiency of these methods.

DD FORM 1 NOV 65 1473 (PAGE 1)
S/N 0101-807-6811

Unclassified
Security Classification

A-31408

14 KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
Replenishment at sea						
Maneuvering control						
Path keeping control						
Distance keeping control						
Interaction Effects						

Thesis
S168
c.1

138058

Sarzetakis
Maneuvering control
of replenishment at sea

20 APR 73 21031
15 DEC 79 25210
21 JAN 81 26819
19 MAY 87 33307

Thesis
S168
c.1

138058

Sarzetakis
Maneuvering control
of replenishment at sea.

thesS168
Maneuvering control of replenishment at
3 2768 001 00167 0
DUDLEY KNOX LIBRARY